Exhibit A – Part 2

(TimeBase's United States Patent No. 6,233,592 B1, "System for Electronic Publishing")

to

TimeBase's Memorandum in Support of Its Motion to Clarify the Claim Construction as it Relates to Summary Judgment

70

-46-

Sunset provision 207. This Part ceases to be in force at the **(j)**end of 5 years after the Parliamentary Joint Committee is first appointed.

Examples of expiry of a portion of a REGULATION

FEDERAL COURT RULES Updated as at 22 March 1996 ORDER 75 NATIVE TITLE RULES 10 NATIVE TITLE ACT 1993 ORDER 75 RULE 21 Sunset provision 15 21. Order 75 ceases to be in force on 1 March 1997. MIGRATION (1993) REGULATIONS - Updated as at 25 July 1994 REG 2A 20 10A Sunset provision 2A.10A. No application may be made under this Division on or after 1 July 1993. 25

[B 06]Type Field

This Field provides more specific information about the type of legislation. It is different to the ID Field described above which gives the legislation a unique ID.

This Field uses three single character codes to describe the legislation.These are as follows:

P = Principal ACTS or REGULATIONS.

It indicates that this is the main or Principal ACT or REGULATION.

35 OR In other words the ACT or REGULATION which gets amended.

Principal ACTS or REGULATIONS can be either in existence (enacted in previous years) or newly enacted (created in the current year).

366274US

IN:\LIBCC]01206US.DOC:IAD

-47-

There is nothing specifically unique or different in a principal ACT or REGULATION that makes it easy to identify. By elimination it is however, possible to say what is not a Principal ACT or REGULATION. This is done by looking at the ACT or REGULATION'S title information. Amending

- 5 Acts or Regulations (which are dealt with <u>next</u>) usually contain the word's "Amending", "Amendment", "Repeal" or "Statute Law Revision" in their Short Title. Another indicator in the case of ACTS is that the Long Title will also contain the word's "Amending", "Amendment", "Repeal" or "Statute Law Revision" (REGULATIONS however, do not have a Long Title).
- The example marked (K) and (J) below shows the Long and Short Titles for a Principal Act known as the Trade Practices Act. (Compare these examples with the ones marked (L) and (M) below).

LONG TITLE(K) An Act relating to certain Trade Practices PART I-PRELIMINARY SECT 1 Short title(J) 1. This Act may be cited as the Trade Practices Act 1974.*1* SEE NOTES TO FIRST ARTICLE OF THIS CHAPTER .

Note: A principal ACT or REGULATION can contain amendments to other ACTS or
 REGULATIONS. It therefore, still needs to be considered for its effect on other ACTS.
 A = Amending ACTS or REGULATIONS.
 It indicates that this is a changing or Amending ACT or REGULATION.

OR In other words the ACT or REGULATION which does the amending.

- 30 Amending ACTS or REGULATIONS will not generally exist in their own right in the consolidated information for which we are creating the data base. The changes they effect will nearly always become part of the Principal ACT or REGULATION.
- There are some rare exceptions to the above point however, which will need to be identified (the way to do this most effectively will be to identify them in Australia and provide a list or table of what these ACTS and REGULATIONS are).

As already stated the best ways to identify an Amending ACT or REGULATION are:

366274US

```
-48-
```

Amending ACTS or REGULATIONS will nearly always contain the word's "Amending", "Amendment", "Repeal" or "Statute Law Revision" in their Short Title.

For Acts (but not Regulations) there is also a Long Title at the very beginning of the Act (usually 5 before Section 1) which will also contain the word's "Amending" "Amendment", "Repeal" or "Statute Law Revision".

The example marked (L) and (M) below shows the Long and Short Titles for the Amending ACT known as the Trade Practices (Secondary Boycotts) Amendment Act 1979. 10

LONG TITLE(L) An Act to amend the Trade Practices Act 1974 with respect Secondary Boycotts and other industrial practices. PART I-PRELIMINARY SECT 1 Short title(M) 1. This Act may be cited as the Trade Practices (Secondary 20 Boycotts) Amendment Act 1979.*1* SEE NOTES TO FIRST ARTICLE OF THIS CHAPTER .

Note: An Amending ACT or REGULATION can be amended itself by a further amending ACT or REGULATION.

More Examples of Amending ACTS and REGULATIONS

Following are some more examples of Amending ACTS and REGULATIONS and what to look for.

30

35

25

15

Statute Law Revision Acts

Below are two examples of these. Usually, this is clean up legislation which makes many changes and often effects a larger number of ACTS. They can be specific as in the case of the Decimal Currency example or they can be general as in the case of the 1973 example.

They can both change (amend Parts, Divisions and Sections of ACTS and REGULATIONS) and/or delete (repeal) whole ACTS and REGULATION or Parts, Divisions and Sections.

366274US

76

-49-

Statute Law Revision (Decimal Currency) Act 1966 Statute Law Revision Act 1973

5 There are other form of Amending ACT similar to the Statute Law Revision Acts as follows:

A.C.T. Self-Government (Consequential Provisions) Regulations 1989 No. 3

Defence Legislation Amendment Act 1984

- 10 Fringe Benefits Tax (Miscellaneous Provisions) Act 1986 Statute Law (Miscellaneous Provisions) Act (No. 1) 1986 Taxation Laws Amendment Act (No. 3) 1986
- The above can usually be spotted by the use of words such as "Consequential Provisions" "Laws Amendment", "Legislation Amendment", "Miscellaneous Provisions" in their Short Titles.

Repeal Acts

Below are two examples of these. One where the term Legislation is used in the title indicating that more many ACTS are being repealed. Again this is often clean up legislation which repeals many ACTS whose purpose or reason for being has lapsed. Alternatively, as the second example indicates Repeal ACTS can be specific, effecting the repeal of only one ACT.

25 Egg Export Legislation Repeal Act 1984 National Welfare Fund Repeal Act

N = Not known

30

Indicates that the type of the ACT or REGULATION is not known or cannot be deterimined. These records will the be handled in Australia.

[B 07]Reprint No Field

The information required for this field does not appear in the Commonwealth Data as presently supplied to/held by us. It will need initially to be obtained in the form of a list of existing reprints and

their numbers and be added to both the Commonwealth data and the data base as a once only job. It will then need to be maintained on a monthly basis using the two AGPS Pamphlet Publications known as ACTS TABLES for Acts and STATUTORY RULES TABLES for Regulations, the last page in each contains this information for the current year. Note: where the

366274US

-50-

Pamphlets are not available or the reprint number is not known or unavailable then the number 999 should be used to indicate this.

Each of the two tables from the Pamphlets contains the name of the Reprinted ACT or REGULATION in alphabetical order (but see Statutory Rules example below) followed by the date of reprint, then followed by the words "Reprint No." and a number. It is this last number that needs to be entered.

ACTS TABLE entry example

10

15

National Health Act 1935 (20 September 1996) Reprint No. 5

STATUTORY RULES TABLE entry example

Note: Statutory Rules are listed by their parent Act (the Act under which the are made appearing in Italic as shown in the example below).

Banks (Shareholdings) Act 1972 --

Banks (Shareholdings) Regulations (2 August 1995) Reprint No. 2

20 [B 08] Reprint Date Field

Like the Reprint Number discussed in **[B 07]** above the information required for this field does not appear in the Commonwealth Data as presently supplied to/held by us. It too will need initially to be obtained in the form of a list of existing reprints and be added to both the Commonwealth data and the data base as a once only job. It will then need to be maintained on a monthly basis using

the two AGPS Pamphlet Publications known as ACTS TABLES for ACTS and STATUTORY RULES TABLES for Regulations, the last page in each contains this information for the current year.

Each of the two tables contains the name of the Reprinted ACT or REGULATION in alphabetical order (but see Statutory Rules example below) followed by the date of reprint, then followed by the words "Reprint No." and a number.

For this field it is the Date preceding the Reprint Number that needs to be entered. For examples see the examples at **[B 07]** above.

35

Note: Again where the Pamphlets are not available or the reprint date is not known or unavailable then the date 00/00/00 should be used to indicate this.

366274US

-51-

[C] TEXTBLOCK TABLE

[C 01] When the should it be used?

TEXTBLOCK entries will not normally be required for ACTS or REGULATIONS which are either

5 Principal or Reprinted ACTS or REGULATIONS. But note that in the case of Principal ACTS there are exceptions, namely; where the Principal ACT or REGULATION also amends or repeals other ACTS or REGULATIONS.

[C 02]ID FIELD

10 This field simply repeats the information obtained in **[B 01]** above. Its purpose is to link this Table with the MASTER TABLE by way of the same ID. For the example, in **[B 01]** for the Social Security Act the ID was **Act-19910046**. This ID would be repeated in this field.

[C 03]Textblock ID1

15 This field is for the ID of the specific Part, Section or regulation in an Amending ACT or REGULATION that causes a change (amendment) to happen.

Textblock ID2 (see **[C 04]** *below*) on the other hand records the ID of the specific Part, Section or regulation in an Amending Act or Regulation that is changed (amended).

EXAMPLE 1

Following is an example of an amendment to the Social Security Act which shows how the information required for this field is obtained.

- 25 Please note there are several ways in which Amending ACTS and REGULATIONS are presented. However, the information required for this ID field is present in all cases. This first example shows the things to look for and the next example show some of the variations possible.
 - (N) The first thing required is an indication as to type. The example is an Amending Act.
- (0) The second thing required is the relevant year. In the example this is <u>1995</u>.
 - (P) The third thing required is the Act or Reg Number. In this example this is <u>104</u>.

(Q) The fourth thing required is the specific Part, Section or regulation doing the amending. In this example this is SCH1 (ie: Schedule 1).

35 The ID entry for this example would then be as follows: ACT-19950104-SCH-1

Social security legislation (N)Amendment act (No. 1) (O)1995 No. (P)104 of 1995 -

366274US

[N:\LIBCC]01206US.DOC:IAD

20

82

-52-

. (Q)SCHEDULE 1 Section 4< AMENDMENT OF THE SOCIAL SECURITY ACT 1991 RELATING TO< THE DEFINITION OF INCOME< 1. After Paragraph 8(8)(zf):< 5 Insert:< "(zfa) a payment of financial supplement made to the person< under the Student Financial Supplement Scheme;".< EXAMPLE 2 10 This example shows a different style of amendment to Example 1. The ID entry for this example would be as follows: ACT-19950105-SEC-4 It would be made up of the following: 15 (R) Indication of Amending Act. (This would be Reg if we were dealing with a Regulation). (S) Year of Act is 1995. (T) Act or Reg Number is 105. (U) Specific Part, Section or regulation doing the amending is SEC4. Note: there is no reference to a Schedule (SCH) because Section 4 is doing the amending. 20 SOCIAL SECURITY (NON-BUDGET MEASURES) LEGISLATION (R)AMENDMENT ACT (S)1995 No. (T)105 of 1995 \$\$NSECT $\left(\mathsf{U} \right)_{4}.$ Section 198 of the Principal Act is amended by inserting after subsection 25 (1A): \$\$P "(1B) Subject to subsection (1C), if:< 30 (a) a person (the 'carer') is personally providing constant care for a severely handicapped person; and< (b) the handicapped person is temporarily absent from Australia for a period of not more than 3 months; and< (c) the carer accompanies the handicapped person on his or her absence from 35 Australia:< the carer does not cease to be qualified for a carer pension merely because of that absence from Australia. \$\$P

366274US

IN:ALIBCC101206US.DOC:IAD

84

-53-

"(1C) If, during a calendar year, the carer has accompanied the handicapped person outside Australia on more than one occasion, the carer ceases to be qualified for carer pension under subsection (1B) in that calendar year after he or she has, during that calendar year, qualified for carer pension under that subsection for periods that together add up to 3 months.".

\$\$A

[C 04]Textblock ID2

10

15

5

This field is for the ID of the specific Part, Section or regulation in an Amending ACT or REGULATION that is changed (amended).

Textblock ID1 (see **[C 03]** *above*) on the other hand records the ID of the specific Part, Section or regulation in an Amending ACT or REGULATION that causes a change (amendment) to happen.

EXAMPLE 1

Following is an example of an amendment to the Social Security Act which shows how the information required for this field is obtained.

20 Please note, as with Textblock ID1, there are several ways in which Amending ACTS and REGULATIONS are presented. However, the information required for this ID field is present in all cases. This first example shows the things to look for and the next example shows some of the variations possible.

25 (V) Again the first thing is an indication as to type. The example is an Amending Act.

(W) The second thing required is the relevant year. In the example this is <u>1991</u>.

(X) The third thing required is the Act or Reg Number. In this example this is <u>46</u>.

(Y) The fourth thing required is the specific Part, Section or Regulation that is being amended. In this example this is SEC8.

30

The ID entry for this example would then be as follows: ACT-19910046-SEC-8

SOCIAL SECURITY LEGISLATION AMENDMENT ACT (No. 1) 1995 No. 104 of 1995 -

35

SCHEDULE 1 Section 4<
AMENDMENT OF THE SOCIAL SECURITY (V)ACT (W)1991

366274US

-54-

(X) [if not available/reproduced in the Amendment text can be obtained from the main ID field in MASTER TABLE]

THE DEFINITION OF INCOME<

After Paragraph (Y)8(8)(zf):

"(zfa) a payment of financial supplement made to the person< under the Student Financial Supplement Scheme;".<

10

5

EXAMPLE 2

Insert:<

This example shows a different style of amendment to Example 1. The ID entry for this example would be as follows: **ACT-19950105-SEC-198**

15 It would be made up of the following:

(Z) Indication of Amending <u>ACT</u>. (This would be Reg if we were dealing with a REGULATION).
 (AA) Year of ACT is <u>1991</u>.
 (BB) The third third equivalent the ACT as DECULATION Number.

 $(\ensuremath{\mathsf{BB}})$ The third thing required is the ACT or REGULATION Number.

In this example this is 46.

20 (CC) Specific Part, Section or regulation being amended is SEC198.

SOCIAL SECURITY (NON-BUDGET MEASURES) LEGISLATION AMENDMENT ACT 1995 No. 105 of 1995

(Z) (AA) (BB) [if not available/reproduced in the Amendment text can be obtained from the main ID field in MASTER TABLE]

\$\$NSECT

4. Section (CC)198 of the Principal Act is amended by inserting after subsection (1A):

\$\$P

<

30

35

25

"(1B) Subject to subsection (1C), if:< (a) a person (the 'carer') is personally providing constant care for a severely handicapped person; and<

(b) the handicapped person is temporarily absent from Australia for a period of not more than 3 months; and

(c) the carer accompanies the handicapped person on his or her absence from Australia;<</p>

366274US

88

-55-

the carer does not cease to be qualified for a carer pension merely because of that absence from Australia. \$\$P

5

<

"(1C) If, during a calendar year, the carer has accompanied the handicapped person outside Australia on more than one occasion, the carer ceases to be qualified for carer pension under subsection (1B) in that calendar year after he or she has, during that calendar year, qualified for carer pension under that subsection for periods that together add up to 3 months.".

10 \$\$A

15

20

[C 05]Date of Commencement Field

This field is for the date an amendment or repeal of a specific Part, Section or regulation commenced. See also **[B 04]** for information on commencement.

EXAMPLE

Below is an example of a commencement provision from an amending ACT. Note how various sections of the amending ACT are allocated a date of commencement. Using the Section identified in TEXTBLOCK ID1 the date of commencement can be identified and entered in this field.

Thus if the TEXTBLOCK ID1 field were **ACT-19950105-SEC-8** then the date information required for this field would be 1 July 1995. See **(DD)** below.

```
25 SOCIAL SECURITY (NON-BUDGET MEASURES) LEGISLATION AMENDMENT ACT 1995 No. 105 of
1995 - SECT 2<
Commencement<
30 $$T
30 $$NSECT
2.(1) Subject to this section, this Act commences on the day on which it
receives the Royal Assent.
$$P
35 <
(2) Subdivision A of Division 2 of Part 2 is taken to have commenced on 1 July
1993.
$$P
```

366274US

90

```
-56-
```

```
(3) Sections 8 and 9 are taken to have commenced on (DD)1 July 1995.
$$P
(4) Section 10 is taken to have commenced on 1 April 1993.
```

[C 06]Date of Expiry Field

This field provides for amendments that are enacted for a period of time, for example; during a special event such as the Olympics.

Note: Expiry provisions are rare and should only be added if clearly specified in the data as in the example below.

15 EXAMPLE

5

See (EE) below.

OLYMPIC SECURITY (NON-BUDGET MEASURES) LEGISLATION AMENDMENT ACT 1997 No. 109 of 1995

\$\$NSECT

4. Section 298 of the Principal Act is amended for the period commencing at midnight on 1 July 1997 and ending on midnight (EE)25 July 1997 by inserting after subsection (2A):

```
25 $$P
```

20

"(2B) Subject to subsection (2C), if:<

(a) a person (the 'carer') is personally providing constant care for a severely handicapped person; and

30 (b) the handicapped person is temporarily absent from Australia for a period of not more than 3 months; and
(c) the carer accompanies the handicapped person on his or her absence from Australia;

the carer does not cease to be qualified for a carer pension merely because of that absence from Australia.

35

\$\$P <

366274US

-57-

"(2C) If, during a calendar year, the carer has accompanied the handicapped person outside Australia on more than one occasion, the carer ceases to be qualified for carer pension under subsection (1B) in that calendar year after he or she has, during that calendar year, qualified for carer pension under that subsection for periods that together add up to 3 months.". \$\$A

5

366274US

Tanaz Appendix d

Keying Guide for Australian Legislation Documents

-58-

General Validation

5

10

15

20

30

All files produced must be parsed against the relevant DTD and each table should be viewed using a suitable Table renderer to make sure that they have been coded correctly.

DTD modifications

No local modifications must be made to the supplied DTD's. If there are any situations in which it is thought that a change to a DTD is required then the requested change and the reasons for it must be submitted to SGMLSE. If a change is deemed necessary, then

the DTD will be changed in the UK and resupplied. This is necessary to maintain consistency in the DTD's being used at both ends in the process. **Files**

The SGML files that will be supplied have already been partially processed but will be invalid according to the DTD (especially the tables).

Each file should omit the document type declaration and begin directly with the root element.

Carriage return characters

Carriage return characters must not appear in any element which has #PCDATA within its content model. If it is wished to use carriage return characters to shorten line lengths,

then they must be placed in positions where they will be ignored by an SGML parser e.g. in places where #PCDATA is not allowed, or within start and end tags in places where separator characters are allowed.

Case

Element and attribute names are case-insensitive. They may be entered in either uppercase, lowercase or a mixture.

Attribute values are usually case-insensitive. The only time that they are case-sensitive is when they have a declared type of CDATA, in which case the string values should be entered directly as they appear in the text.

بار

366274US

-59-

Markup minimisation

No non-empty elements have omissible start or end tags, but the empty end tag </> can be used to end the currently open element. A carriage return character can not occur within an empty end tag.

5 **DTD structure**

There are four DTDs and a common element declaration that are used to define the structure of the legislation.

REGS.DTD

10

25

This DTD has the public identifier "-//SGMLSE//DTD 1.0 Regulations//EN" and contains the declaration for the regulations. It has two parameter entity references which include "-//SGMLSE//DTD 1.0 Act//EN" and "-//SGMLSE//DTD 1.0 Regulation//EN".

The file *regs.sgm* produced by the Perl script *regs.pl* conforms to regs.dtd and calls in all acts as parameter entities.

ACTS.DTD

This DTD has the public identifier "-//SGMLSE//DTD 1.0 Acts//EN" and contains the declaration for the acts. It has a parameter entity references which includes "-//SGMLSE//DTD 1.0 Act//EN".

The file *acts.sgm* produced by the Perl script *acts.pl* conforms to acts.dtd and calls in all acts as parameter entities.

20 **ACT.DTD**

This DTD has the public identifier "-//SGMLSE//DTD 1.0 Act//EN" and contains the declaration of an act.

REG.DTD

This DTD has the public identifier "-//SGMLSE//DTD 1.0 Regulation//EN" and contains the declaration of a regulation.

COMMON.ELT

This list of elements has the public identifier "-//SGMLSE//ELEMENTS 1.0 Common Elements//EN" and includes element and entity definitions common to all document types.

30 Character entities

The character entities allowed have been selected from the ISO public sets isogrk1, isogrk3, isolat1, isonum, isopub and isotech.

These characters are translated one-to-one to the equivalent character in the Times New Roman True Type font.

The <quote> or <blockquote> elements should be used instead to surround any quoted text.

Use Quotes (") at the beginning and at the end of these elements.

366274US

-60-

Labels and identifiers

The major structural elements - act, reg, part, schedule, section, sub, s-sub, ss-sub, ... all have a required label attribute (Ibl). Unique identifiers should be generated for these

```
elements. The label for these elements is the preceding number or letter WITHOUT any
 5
     punctuation or parentheses. For example :
     1979 No. 141 The charge to income tax - REG 1
     Income Tax
     1. Fred ...
     1. (1) This is ...
10
     <section type="reg" lbl="1" ID="CWACT-19790141-SEC-1">
     <title>Income Tax</>
     <list>
     <1i lbl="1">Fred ...</>
15
    <list>
     lbl="1">This is ...</>
     </list>
     </list>
    </section>
20
     Convert list and li items back to the original look in Folio Views, ie to
     1. Fred ...
    1. (1) This is ...
     Cross references
25
    All cross references point directly to a target by providing the id of the target as the value
     of an attribute of the xref element. For details of the format of cross reference identifier
     strings, see the description of the xref element below.
```

All ID's are marked unchanged as Jump Destinations (JD's). <SECTION ID="CWACT-19950104-SEC-1" LBL="1">

REGS DTD ELEMENT REGS

35 This is the root element of the Regulations. Its definition is :

<!ELEMENT regs - - (title, header?, reg+) >

That is, it contains a required title element, followed by an optional header element followed by 1 or more act element.

366274US

Not translated

99

ACTS DTD ELEMENT

ACTS

5 This is the root element of the Acts. Its definition is : <!ELEMENT acts - (title, header?, act+) > That is, it contains a required title element, followed by an optional header element followed by 1 or more act element. Not translated

10 REG DTD ELEMENTS

REG

15

20

30

This is the root element of the dtd for a Regulation. Its definition is :

```
<!ELEMENT reg - - (title, notes?, provisions?, (preamble long-
title)?,
((order+|(section|schedule)+|chapter+|part+),schedule*))>
<!ATTLIST
             reg id ID #REQUIRED
                lbl
                              CDATA
                                      #REQUIRED
             insert-date NUMBER #IMPLIED
                              IDREF
                                           #IMPLIED
             insert-leg
             repeal-date NUMBER
                                  #IMPLIED
             repeal-leg
                              IDREF
                                           #IMPLIED
             amend-date
                         NUMBER
                                  #IMPLIED
                                           #IMPLIED
             amend-leg
                              IDREF
```

The insert-date attribute should be used to insert the date YYYYMMDD that the REG was inserted. The insert-leg should be used to insert the ID of the legislation that inserted the REG.

The repeal-date attribute should be used to insert the date YYYYMMDD that the REG was repealed. The repeal-leg should be used to insert the ID of the legislation that repealed the REG.

The amend-date attribute should be used to insert the date YYYYMMDD that the REG was amended. The amend-leg should be used to insert the ID of the legislation that amended the REG.

The title gets marked up as Level "Heading Level 1". The period between the insert-date and the repeal-date or amend-date (that is the period during which the above element was in force) gets marked up as follows:

The Folio Views markup used is Groups. See the manual for explanations. We will use three kinds of groups: Inforce-yyyy, Inforce-yyyy-mm and Inforce-yyyy-mm-dd (yyyy can

be any year, mm can be any month from 1 - 12 and dd can be any day from 1 - 31). If the element was valid throughout a year yyyy, the element becomes a member of the Inforceyyyy group. If the element was valid only for some months within a year, it becomes a member of the relevant Inforce-yyyy-mm groups. If the element was only valid for some days within a month, the element becomes a member of the relevant Inforce-yyyy-mm-dd

groups. Example:

5

10

15

20

If the element was valid from 1/7/94 to 7/4/96, then the element belongs to the following groups:

Inforce-94-07, Inforce-94-08, Inforce-94-09, Inforce-94-10, Inforce-94-11, Inforce-94-12, Inforce-95, Inforce-96-01, Inforce-96-02, Inforce-96-03, Inforce-96-04-01, Inforce-96-04-02, Inforce-96-04-03, Inforce-96-04-04, Inforce-96-04-05, Inforce-96-04-06 and Inforce-96-04-07.

Note that the element is not part of the Inforce-94 group because the element wasn't in force throughout of 1994. Nor is the element part of the Inforce-96-04 group because the element wasn't in force throughout April 1996.

If the enduser wants to search for all elements that are valid as of a particular date then the enduser can enter that date in a Query Template in the form DD/MM/YYYY. The Query Template then searches the Folio Views infobase for all elements that belong to the groups Inforce-yyyy, Inforce-yyyy-mm and Inforce-yyyy-mm-dd.

ACT DTD ELEMENTS

ACT

```
This is the root element of the dtd for an Act. Its definition is :
    <!ELEMENT act - - (title, notes?, provisions?, (preamble long-
    title)?, (section+|chapter+|part+|sub+)*, schedule*)>
25
                   act id ID #REQUIRED
    <!ATTLIST
                      date CDATA #IMPLIED
                   insert-date NUMBER
                                           #IMPLIED
                   insert-leg
                                      IDREF
                                                     #IMPLIED
30
                   repeal-date NUMBER
                                           #IMPLIED
                                                     #IMPLIED
                   repeal-leg
                                      IDREF
                   amend-date
                                 NUMBER
                                           #IMPLIED
                   amend-leg
                                      IDREF
                                                     #IMPLIED
    That is, it contains a required title element, followed by optional notes, provisions, and
35
```

That is, it contains a required title element, followed by optional notes, provisions, and preamble and either one or more reg, order, rule, section, chapter or part elements. It has a required id attribute and implied date attribute

366274US

```
-63-
```

The insert-date attribute should be used to insert the date YYYYMMDD that the ACT was inserted. The insert-leg should be used to insert the ID of the legislation that inserted the ACT.

The repeal-date attribute should be used to insert the date YYYYMMDD that the ACT

5 was repealed. The repeal-leg should be used to insert the ID of the legislation that repealed the ACT.

The amend-date attribute should be used to insert the date YYYYMMDD that the ACT was amended. The amend-leg should be used to insert the ID of the legislation that amended the ACT.

10 Examples

```
1979 No. 141 The charge to income tax
<act lbl="141" ID="CWACT-19790141-TXT-0">
<title>1979 No. 141 The charge to income tax</>
1979 No. 141 The charge to income tax</>
<act lbl="141" ID="CWACT-19790141-TXT-0">
<title>1979 No. 141 The charge to income tax<noteref ref="CWACT-
19790141-note-1"></>
The noteref gets marked up as a popup link. The text of the note becomes the text within
the popup link.
```

20

25

30

15

```
Treated the same as Reg DTD Elements. See there for details.
COMMON ELEMENTS
```

PART

```
<!ELEMENT part - - (title, (%plevel;)*,
(chapter+|division+|section+)*, notes?)
            partid ID #REQUIRED
<!ATTLIST
                 1b1 CDATA #IMPLIED
                 insert-date
                                  NUMBER
                                                #IMPLIED
                 insert-leg
                                  IDREF
                                                #IMPLIED
                                                #IMPLIED
                 repeal-date
                                  NUMBER
                 repeal-leg
                                  IDREF
                                                #IMPLIED
                 amend-date
                                  NUMBER
                                                #IMPLIED
                 amend-leg
                                  IDREF
                                                #IMPLIED
```

The insert-date attribute should be used to insert the date YYYYMMDD that the PART was inserted. The insert-leg should be used to insert the ID of the legislation that inserted the PART.

366274US

```
-64-
```

The repeal-date attribute should be used to insert the date YYYYMMDD that the PART was repealed. The repeal-leg should be used to insert the ID of the legislation that repealed the PART.

The amend-date attribute should be used to insert the date YYYYMMDD that the PART was amended. The amend-leg should be used to insert the ID of the legislation that

amended the PART.

```
Example
```

```
<PART lbl="1" ID="CWACT-19790141-PT-1">
<title></title>
```

10

15

20

5

The title gets marked up as Level "Heading Level 2". Dates get treated the same way as in Regs DTD Elements. See there for details.

ORDER

<

```
<!ELEMENT order - - (title,
```

```
(division|section|part|schedule)+)>
```

!ATTLIST	order id ID #R	EQUIRED	
	lbl CDATA #IMPLIED		
	insert-date	NUMBER	#IMPLIED
	insert-leg	IDREF	#IMPLIED
	repeal-date	NUMBER	#IMPLIED
	repeal-leg	IDREF	#IMPLIED
	amend-date	NUMBER	#IMPLIED
	amend-leg	IDREF	#IMPLIED

>

The insert-date attribute should be used to insert the date YYYYMMDD that the ORDER was inserted. The insert-leg should be used to insert the ID of the legislation that inserted the ORDER.

The repeal-date attribute should be used to insert the date YYYYMMDD that the ORDER was repealed. The repeal-leg should be used to insert the ID of the legislation

30 that repealed the ORDER.

The amend-date attribute should be used to insert the date YYYYMMDD that the ORDER was amended. The amend-leg should be used to insert the ID of the legislation that amended the ORDER.

Example

35 1979 No. 140 FEDERAL COURT RULES - ORDER 3<

ORDER 3< TIME<

\$\$T

366274 U S

[N:\LIBCC]01206US.DOC:IAD

a due de la de la de la de due due due de la de la de la de

```
-65-
```

```
$$A
    $$T
    1979 No. 140 FEDERAL COURT RULES - RULE 1<
    <ORDER lbl="3" ID="CWACT-19790140-ORD-3">
    <title>TIME</title>
    <section type="rule" lbl="1" ID="CWACT-19790140-ORD-3.1">
    The title gets marked up as Level "Heading Level 2". Dates get treated the same way as
    in Regs DTD Elements. See there for details.
    DIVISION
    <! ELEMENT
10
                  division - - (title, (sub-division+ | section+)) >
    <!ATTLIST
                  division id ID #REQUIRED
                  1b1 CDATA #IMPLIED
                  insert-date
                                    NUMBER
                                                   #IMPLIED
                  insert-leq
                                     IDREF
                                                   #IMPLIED
                  repeal-date
                                     NUMBER
                                                   #IMPLIED
                  repeal-leg
                                     IDREF
                                                   #IMPLIED
                  amend-date
                                     NUMBER
                                                   #IMPLIED
                                     IDREF
                  amend-leg
                                                   #IMPLIED
    >
```

- The insert-date attribute should be used to insert the date YYYYMMDD that the 20 DIVISION was inserted. The insert-leg should be used to insert the ID of the legislation that inserted the DIVISION.
 - The repeal-date attribute should be used to insert the date YYYYMMDD that the DIVISION was repealed. The repeal-leg should be used to insert the ID of the legislation that repealed the DIVISION.
 - The amend-date attribute should be used to insert the date YYYYMMDD that the DIVISION was amended. The amend-leg should be used to insert the ID of the legislation that amended the DIVISION.

Example

1979 No. 140 FEDERAL COURT RULES - DIVISION 1< 30

Division 1-General<

\$\$T

\$\$A

- \$\$T
- 1979 No. 140 FEDERAL COURT RULES RULE 1< 35 Cases for service of originating process< <DIVISION lbl="1" ID="CWACT-19790140-DIV-1> <title>General</title>

366274US

IN:\LIBCC101206US.DOC:IAD

5

15

25

-66-

<RULE lbl="1" ID="CWACT-19790140-DIV-1.1">

<title> Cases for service of originating process </title>

The title gets marked up as Level "Heading Level 3". Dates get treated the same way as in Regs DTD Elements. See there for details.

5 SUB-DIVISION

< ! ELEMENT	sub-division	(title, sect	ion+) >
ATTLIST</td <td>sub-division id I</td> <td>ID #REQUIRED</td> <td></td>	sub-division id I	ID #REQUIRED	
	lbl CDATA #IMPLI	ED	
	insert-date	NUMBER	#IMPLIED
	insert-leg	IDREF	#IMPLIED
	repeal-date	NUMBER	#IMPLIED
	repeal-leg	IDREF	#IMPLIED
	amend-date	NUMBER	#IMPLIED
	amend-leg	IDREF	#IMPLIED

15

20

>

10

The insert-date attribute should be used to insert the date YYYYMMDD that the SUB-DIVISION was inserted. The insert-leg should be used to insert the ID of the legislation that inserted the SUB-DIVISION.

The repeal-date attribute should be used to insert the date YYYYMMDD that the SUB-

DIVISION was repealed. The repeal-leg should be used to insert the ID of the legislation that repealed the SUB-DIVISION.

The amend-date attribute should be used to insert the date YYYYMMDD that the SUB-DIVISION was amended. The amend-leg should be used to insert the ID of the legislation that amended the SUB-DIVISION.

25 The title gets marked up with a Paragraph Style (see Folio Views Infobase Production Kit Manual for details) 'Subdivision'. Dates get treated the same way as in Regs DTD Elements. See there for details.

PROVISIONS

<!ELEMENT provisions - - (title, tblblk) >

30 Example

\$\$NTABLE

TABLE OF PROVISIONS<

\$\$P Order<

35 \$\$P

1. Preliminary<

\$\$P

2. Sittings and Vacation<

366274US

```
-67-
```

```
<PROVISIONS>
<TITLE>TABLE OF PROVISIONS>
<TBLBLK>
..
</TBLBLK>
```

</PROVISIONS>

5

10

15

20

Provisions get ignored. The Table of Provisions gets generated by the conversion program from the following Elements: Part, Chapter, Order, Division, Subdivision and Section. The generated Table of Provision is stored just before the first Part, Chapter, Order, Division, Subdivision and Section.

CHAPTER

<!ELEMENT chapter - - (title, (%plevel;)*, (part+|section+|article+)?)> <!ATTLIST chapter id ID #REQUIRED 1bl CDATA #IMPLIED insert-date NUMBER #IMPLIED insert-leg IDREF #IMPLIED repeal-date #IMPLIED NUMBER repeal-leg IDREF #IMPLIED amend-date NUMBER #IMPLIED amend-leg IDREF #IMPLIED >

The insert-date attribute should be used to insert the date YYYYMMDD that the CHAPTER was inserted. The insert-leg should be used to insert the ID of the legislation

25 that inserted the CHAPTER

The repeal-date attribute should be used to insert the date YYYYMMDD that the CHAPTER was repealed. The repeal-leg should be used to insert the ID of the legislation that repealed the CHAPTER.

The amend-date attribute should be used to insert the date YYYYMMDD that the CHAPTER was amended. The amend-leg should be used to insert the ID of the

```
30 CHAPTER was amended. The amend-leg should be used to insert the ID of the
legislation that amended the CHAPTER.
```

The title gets marked up as Level "Heading Level 2". Dates get treated the same way as in Regs DTD Elements. See there for details.

35 SECTION

```
This is a sub element of a Regulation. Its definition is :
<!ELEMENT section - - (title, (%unstruct-cont;))>
<!ATTLIST section id ID #REQUIRED</pre>
```

366274US

```
-68-
```

lbl CDATA #IMPLIED		
insert-date	NUMBER	#IMPLIED
insert-leg	IDREF	#IMPLIED
repeal-date	NUMBER	#IMPLIED
repeal-leg	IDREF	#IMPLIED
amend-date	NUMBER	#IMPLIED
amend-leg	IDREF	#IMPLIED

That is, it contains a required title element, followed by unstructured content. It has a required lbl attribute and a required id attribute.

The insert-date attribute should be used to insert the date YYYYMMDD that the SECTION was inserted. The insert-leg should be used to insert the ID of the legislation that inserted the SECTION.

The repeal-date attribute should be used to insert the date YYYYMMDD that the SECTION was repealed. The repeal-leg should be used to insert the ID of the legislation that repealed the SECTION.

The amend-date attribute should be used to insert the date YYYYMMDD that the SECTION was amended. The amend-leg should be used to insert the ID of the legislation that amended the SECTION.

```
    Examples
    1979 No. 141 The charge to income tax - SECT. 1
    Income Tax
    1979 No. 141 The charge to income tax - REG 2
    Tax
```

```
25 3. Income tax shall be charged...
    <section lbl="1" id="CWACT-1979141-SEC-1">
        <title>Income tax</>
        <section type="reg" lbl="2" id="CWACT-1979141-SEC-</pre>
```

```
<section type="reg" ibl="2" id="CwACI-197:
1.2"><title>Tax</title>
```

30 Income tax shall be charged...</>

```
The title gets marked up as Level "Heading Level 4". Dates get treated the same way as in Regs DTD Elements. See there for details.
```

SCHEDULE

This is a sub element of a Regulation. Its definition is :

35 <!ELEMENT schedule - - (title?, (%unstruct-cont;))>

<!ATTLIST schedule id ID #REQUIRED lbl CDATA #IMPLIED insert-date NUMBER

366274US

[N:\LIBCCI01206US.DOC:IAD

#IMPLIED

5

10

```
-69-
```

| insert-leg | IDREF | #IMPLIED |
|-------------|--------|----------|
| repeal-date | NUMBER | #IMPLIED |
| repeal-leg | IDREF | #IMPLIED |
| amend-date | NUMBER | #IMPLIED |
| amend-leg | IDREF | #IMPLIED |
| | | |

That is, it contains a required title element, followed by unstructured content. It has a required lbl attribute and a required id attribute.

The insert-date attribute should be used to insert the date YYYYMMDD that the SCHEDULE was inserted. The insert-leg should be used to insert the ID of the legislation that inserted the SCHEDULE.

The repeal-date attribute should be used to insert the date YYYYMMDD that the SCHEDULE was repealed. The repeal-leg should be used to insert the ID of the legislation that repealed the SCHEDULE.

The amend-date attribute should be used to insert the date YYYYMMDD that the SCHEDULE was amended. The amend-leg should be used to insert the ID of the legislation that amended the SCHEDULE.

Examples

1979 No. 141 The charge to income tax - SCHEDULE 1

20 Income Tax

5

>

1. Income tax shall be charged...

<schedule lbl="1" id="CWACT-1979141-SCH-1">

```
<title>Income tax</>
```

Income tax shall be charged...</>

²⁵ The title gets marked up as Level "Heading Level 2". Dates get treated the same way as in Regs DTD Elements. See there for details.

FORM

<!ELEMENT form- - (title, formreg, front, back?) > <!ATTLIST form%reqlbl;

%reqid;>

Each form has a title, regulation, a front and an optional back. Each has a required lbl attribute and a required ID.

Example

FORM A<

```
35
```

30

Regulation 7<

(Front of Form)<

COMMONWEALTH OF AUSTRALIA< Trade Practices Act 1974-Sub-section 88 (1)<

-70-

EXCLUSIONARY PROVISIONS:< APPLICATION FOR AUTHORIZATION<

To the Trade Practices Commission: Application is hereby made under sub-section 88 (1) of the Trade

5 (Back of Form)<

DIRECTIONS<

1. Where there is insufficient space on this form to furnish the required information, the information is to be shown on separate sheets, numbered consecutively and signed by or on behalf of the applicant.

10 <FORM lbl="a" ID="CWACT-19790141-FORM-A"> <FORMREG>Regulation 7</FORMREG> <FRONT>

<ASIS>

COMMONWEALTH OF AUSTRALIA<

- Trade Practices Act 1974-Sub-section 88 (1)<
 - EXCLUSIONARY PROVISIONS:<
 - APPLICATION FOR AUTHORIZATION<
- To the Trade Practices Commission: Application is hereby made under sub-section 88 (1) of the Trade
- 20 </ASIS>

15

- </FRONT> <BACK> <ASIS>
 - DIRECTIONS<
- Where there is insufficient space on this form to furnish the required information, the information is to be shown on separate sheets, numbered consecutively and signed by or on behalf of the applicant.

</ASIS>

</BACK>

30 </FORM>

Forms get marked up with a Paragraph Style 'Forms'. The markup of 'Front' and 'Back' gets inserted as hidden text (hidden text is visible on the screen but doesn't show when the Form gets printed.

FORM ELEMENTS

35 FORMREG

<!ELEMENT formreg - - (#PCDATA) >
see above example

366274US

```
-71-
```

FRONT <! ELEMENT front - - (asis) > see above example BACK < ! ELEMENT back - - (asis) >see above example ASIS <! ELEMENT asis - - (#PCDATA) > date is displayed as-is see above example 10 HEADER ELEMENTS HEADER < ! ELEMENT header - - (scope?, updated?) > SCOPE <! ELEMENT scope - - (%text;) > 15 UPDATED < ! ELEMENT updated - - (%text;) > NOTE ELEMENTS NOTES < ! ELEMENT - 0 (note+) > 20 notes List of notes at the start of an act NOTE <! ELEMENT note - - (%plevel;) > <!ATTLIST note id ID #REQUIRED> A single note 25 Forms get marked up with a Paragraph Style 'Forms'. The markup of 'Front' and 'Back' gets inserted as hidden text (hidden text is visible on the screen but doesn't show when the Form gets printed. STRUCTURAL ELEMENTS 30

TITLE

A generic title, which may occur in several different contexts. Covered in Acts DTD Elements, Regs DTD Elements and so on.

INLINE ELEMENTS

BOLD 35

> Used to mark any inline text which is set in a bold face other than a title or a label. It may contain text or any inline elements other than <bold>. It has no attributes.

366274US

[N:\LIBCC]01206US.DOC:IAD

ŧ

5

-72-

ILEQN

An inline equation. This is a mathematical equation which is embedded in a line of text characters or other inline elements. See the attached description of equations for further details.

5 ITAL

Used to mark any inline text which is set in a italic face other than a title or a label. It may contain text or any inline elements other than <italic>.

It has no attributes.

QUOTE

10 A sequence of text characters or inline elements surrounded by single or double paired quotation marks. The quotation mark characters must not be entered as text characters or entity references as they will be generated automatically.

SUBSCR

A Subscript (inferior).

15 SUPER

A superscript (superior).

Brought over from SGML to Folio Views with no changes.

CROSS REFERENCES

NOTEREF

A reference to a NOTE element normally used in a TITLE element

Implemented as a popup link.

TEMPREF

A reference to a piece of legislation where the ID is not known. The tempref element will converted to an XREF element at a later date (when the ID is known).

25 Not converted.

RNGREF

A cross reference to a sequential range of targets, e.g. see Sections 3 to 7.

It has two required attributes, startref and endref. Startref is the id of the first of the targets referenced and endref is the id of the last target referenced. For a description of id strings, see the description of the xref element.

30 id strings, see the description of the Converted as a Query Link.

XREF

A cross reference to a single target. It has a single attribute, ref, which must contain the id string of the target of the reference. Ids are not being entered on elements during

keying, but will be generated automatically from the lbl attribute of elements. However, for xrefs it is necessary to work out what the id string of the target will be. The format of id strings is described below :

Converted as a jumplink.

366274US

-73-

ID Strings

Cross references to sections of Acts and Act Schedules should be marked up using the xref element as described above.

5 Id strings are made up of four sequential fields separated by a "-" (dash) character as follows :

```
field1-field2-field3-field4
```

field 1 is the type of document which is being referenced. The current valid value is ACT. field2 is an abbreviated form of the year and number of the Act, e.g. 19880001 is 1988

10 No. 1.

field3 identifies the type of object being referenced. Valid values are :

- ORD order
- DIV division
- SCH schedule in an Act
- 15 SEC section in an Act
 - CH chapter in an Act
 - PT part in an Act
 - NOTE a note

field4 is the identifier of the element being referenced, which is formed by concatenating

the values of the lbl attributes of the referenced element and its ancestor elements, separated by a "." (point) character. e.g. 1 or 1.1 or 1.1.a or 1.1.a.iv

```
Examples
```

25

```
<section lbl="1"><!-- id is ACT-19790141-SEC-1 -->
<title>The charge to income tax.</>
<list>
```

Income tax shall be charged...</>
Implemented as jumpdestination.

BLOCK LEVEL ELEMENTS

DPEQN

A display equation. This is a mathematical equation which is set on one or more lines by itself. See the attached description of equations for further details. It has no attributes.

35 It has no attributes.

LIST

A list of related lines of text which are not sub, s-sub or ss-sub elements.

366274US

-74-

LI

5

15

An item in a list. This is a single line of text within a list.

It has a single attribute, marker, which has allowed values of bullet, dash or none, with a default of none. If a marker character precedes the list item then the relevant value should be entered for the attribute. The marker character should not be entered as text.

If any marker character other than a bullet or dash is found, contact SGMLSE for a change to the DTD.

Ρ

A single line of text. 10 BLOCKQUOTE

A non-inline quote. The quotation mark characters must not be entered as text characters or entity references as they will be generated automatically

TBLBLK

A container element for a table which has a title. It contains a required title element followed by a single table.

It has no attributes.

The above elements get implemented either without conversion or using paragraph styles. TABLE ELEMENTS

General

- 20 Arbortext tables expressed in tagged ASCII form must follow this basic structure:
- <rowrule> for each row { 25 <tablerow> <cellrule> for each column ł <tablecell>text</tablecell> <cellrule> 30 } </tablerow> <rowrule> } 35

366274US

```
-75-
```

TABLE

The tag has three required attributes. They must be specified correctly or the table will not be handled properly.

ncols=NUMBER The number of columns in the table. This value MUST agree with the number of columns expressed by the required cwl attribute.

wdm=(25|50|75|100) The numbers indicate the width of the table as a percentage of the page width.

cwl=LIST where LIST is a list of integers each separated by a colon. Each integer represents the relative width of a column.

10 Example

5

A four column table which is the full width of the page. The second and third columns are twice the width of the first column, and the fourth column is three times the width of the first :

```
15 or, equivalently,
```

CELLRULE

Empty element. Specifies a vertical rule. It has a single attribute, rty, which specifies the type of rule. Valid values for rty are :

n n	(point)	for a blank rule,
"_"	(dash)	for a single rule,

```
"=" (equals) for a double rule,
```

```
"+" (plus) for a bold rule.
```

Example

```
25 <cellrule rty=".">
```

```
for a blank rule, or
```

<cellrule rty="-">

for a single rule.

ROWRULE

30 Empty element. Specifies a sequence of horizontal rules, one per cell in the row. It has a single attribute, rtl, which is a colon-delimited list of rule type specifiers. There must be one rule type specifier for each cell in the row. The valid specifiers are as for cellrule above.

Example

35 For a four-column table

<rowrule rtl="-:.:.'>

would draw a horizontal rule above cells one and four.

366274US

[N:\LIBCC|01206US.DOC:HAD

20

-76-

TABLEROW

Specifies a row in the table. It has a single attribute, hdr, which specifies whether or not the row is a header row in a table which will be repeated over page breaks. The only valid value is "1" (one), which indicates that the row is a header row. An omitted value

5 for hdr indicates that the row is not a header row. A value is only valid on the first <tablerow> in the table.

Example

```
<tablerow hdr="1">
```

indicates that the row is a header row (iff the <tablerow> is the first in the table, else it will generate an error).

<tablerow>

10

indicates that the row is not a header row if the <tablerow> is the first in the table.

TABLECELL

Indicates a cell in a row in a table. It has four optional attributes :

chj=(b|1|r|c) Horizontal justification for that cell.
b for both right and left justified,
1 for flush left,
r for flush right,
c for centred.

20 Default: left justified

cvj=(t c b)	Vertical justification for that cell.
t	for top justified,
с	for centred, or
b	for bottom justified.

Default: top justified

spn=INTEGER For horizontally spanned columns. VAL is a whole number representing how many columns are spanned. Note that for horizontal spans, the text appears in the LEFTMOST cell in the span, and all other cells in the span should be void

30 of text. Default: 1

25

vspn=INTEGER For vertically spanned rows. VAL is a whole number representing how many rows are spanned. Note that for vertical spans, the text appears in the LOWEST cell in the span, and all other cells in the span should be void of text.

35 Default: 1

Arbortext table example

|foo | fum | |

366274US

	_	_	
-	7	7	-

	fee
	spanned ugh
5	<tb></tb> <tb></tb>
	<rowrule rtl="-:"></rowrule>
	<tablerow hdr="1"></tablerow>
10	<cellrule rty="-"></cellrule>
	<tablecell>foo</tablecell>
	<cellrule rty="-"></cellrule>
	<tablecell chj="c">fum</tablecell>
	<cellrule rty="-"></cellrule>
15	<tablecell chj="r" cvj="b">fee</tablecell>
	<cellrule rty="-"></cellrule>
	<rowrule rtl="-:-:"></rowrule>
	<tablerow></tablerow>
20	<cellrule rty="-"></cellrule>
	<tablecell chj="c" spn="2">spanned</tablecell>
	<cellrule rty="-"></cellrule>
	<tablecell chj="c">ugh</tablecell>
	<cellrule rty="-"></cellrule>
25	

30 *Tables get converted to Microsoft Word tables and then converted into Folio Views.* EQUATION ELEMENTS

General

This maths DTD is a subset of the Arbortext maths DTD, which itself is derived from the AAP maths DTD.

In maths mode, all spaces are ignored (except in a <phr> element as described below).
 Correct spacing is handled automatically.

All alphabetical characters and symbols are treated as variables and set in italic face, unless they occur within <phr>>, <rm> or <rf> elements.

{N:\LIBCC101206US.DOC:1AD

All numeric characters and operators are set in roman face, unless they occur within an <it> element.

Greek symbols should be entered using the <g> element rather than entity references. E.g. <g>a</g> produces alpha, <g>b</g> beta, etc. Any entity references for Greek

characters which appear in equations will be flagged as errors by the parsing program.

В

Bold text in an equation.

DE

Denominator of a fraction.

10 **F**

5

Inline equation. **FD**

Display equation.

¹⁵ Fence. A pair of bracketed delimiters. The attribute lp (left post) defines the type of the left delimiter as below, and the following element rp (right post) defines the type of the right delimiter.

```
<!ATTLIST fen lp
                         (par | sqb | cub | ang | vb)
                                                   vb
                                                        - -
               left parenthesis
                                        (
        par
        sqb left square bracket
                                       [
        cub
               left curly brace
                                        {
               left angle bracket
        ang
                                       <
               left vertical bar
                                       1
        vb
```

--> 25 **FR**

20

Fraction.

G

Greek character or characters. Valid characters are :

	char	equivalent entity
30	а	alpha
	b	beta
	с	chi
	d	delta
	D	Delta
35	е	epsilon
	3	epsiv
	4	phiv
	f	phis

-79-

			F	Phi
				gamma
			g G	Gamma
			h	
				eta
	5		i	iota
			j	thetav
			k	kappa
			1	lambda
			L	Lambda
	10		m	mu
			n	nu
1			р	pi
- 540			2	piv
1.00			Р	Pi
	15		q	thetas
-			Q	Theta
10			r	rho
÷.			S	sigma
			S	Sigma
	20		9	rhov
67			t	tau
			u	upsilon
			U	Upsilon
			v	sigmav
	25		w	omega
			W	Omega
			x	xi
			Х	Xi
			у	psi
	30		Y	Psi
			z	zeta
		INF		
		Inferior. IT	Subsci	ript in an equation.
	35	ltalic tex NU	t in an	equation.

Numerator of a fraction.

366274US

-80-

OVL

Overline.

PHR

5

10

Phrase. In a phrase all characters are set in roman face and keyed space characters are preserved. A phrase is essentially a temporary escape out of maths mode back into normal text mode.

RAD

Radical or root. Contains a radicand (<rcd>), which is the constructs which appear beneath the top horizontal bar, and an optional radix (rdx), which is the power of the root (e.g. square, cube, 4, etc.).

RCD

Radicand. The content of a root construct.

RDX

Radix. The power of a root.

15 **RF**

Roman Function. A function name set in roman face, such as log, sin, cos, lim, arg, etc. It differs from the <rm> element in that preceding and following space characters are generated to separate it from surrounding characters.

RM

20 Roman face. Used to force an alpha character to be displayed in normal face rather than be treated as a variable and displayed in italic face.

RP

Right delimiter of a fence. It has a single attribute, post, which defines the type of the delimiter. Valid values are the same as for the lp attribute of the <fen> element, except that they specify the right hand match for the relevant left post.

SUP

25

30

Superior. A superscript in an equation.

UNL

Underline.

Arbortext equation examples

- ... by multiplying by the fraction -
 - Α
 - в

```
where -
```

```
35 <
```

```
... by multiplying by the fraction -</><dpeqn><fr><nu><rm>A</></></><de><rm>B</>></></></></></>
```

366274US

140

```
-81-
```

... by the formula -

<u>gross taxable income</u> net assets

5 ... by the formula -</>
 <dpeqn><fr><nu><phr>gross taxable income</></><de><phr>net
 assets

Equations get converted to Microsoft Word equations and then converted into Folio Views. Alternatively equations get converted to images and added to Folio Views as images.

10

366274US

્ર

-82-Sala APPENDIX E <!SGML "ISO 8879:1986" ArborText's default SGML declaration, modified to allow longer id/idref's, and to use a number of special characters 5 within them. CHARSET BASESET "ISO 646-1983//CHARSET 10 International Reference Version (IRV)//ESC 2/5 4/0" DESCSET 9 UNUSED 0 2 9 9 2 UNUSED 11 15 1 13 13 18 UNUSED 14 95 32 32 127 1 UNUSED 128 "High-order characters" 128 20 CAPACITY SGMLREF TOTALCAP 200000 ENTCAP 35000 ENTCHCAP 35000 25 ELEMCAP 35000 150000 GRPCAP EXGRPCAP 35000 EXNMCAP 35000 ATTCAP 50000 30 ATTCHCAP 35000 AVGRPCAP 35000 35000 NOTCAP NOTCHCAP 35000 IDCAP 35000 35 IDREFCAP 35000 MAPCAP 35000 LKSETCAP 35000 LKNMCAP 35000 40 SCOPE DOCUMENT SYNTAX SHUNCHAR 0 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27 28 29 30 31 127 45 BASESET "ISO 646-1983//CHARSET International Reference Version (IRV)//ESC 2/5 4/0" DESCSET 0 128 0

366274US

144

-83-

		128 128 "High-order characters"
		FUNCTION RE 13 RS 10
		SPACE 32
	5	TABSEPCHAR 9
		NAMING LCNMSTRT ""
		UCNMSTRT ""
		LCNMCHAR "/[]"
		UCNMCHAR "/[]"
	10	NAMECASE GENERAL YES
		ENTITY NO DELIM GENERAL SGMLREF
		SHORTREF SGMLREF
		NAMES SGMLREF
	15	QUANTITY SGMLREF
1773 1420	10	ATTCNT 100
120		ATTSPLEN 960
		BSEQLEN 960
		DTAGLEN 16
	20	DTEMPLEN 16
		ENTLVL 16
		GRPCNT 100
- 		GRPGTCNT 96 GRPLVL 16
	25	GRPLVL 16 LITLEN 800
ra ¹	25	NAMELEN 64
)		NORMSEP 2
		PILEN 1024
		TAGLEN 960
	30	TAGLVL 24
		FEATURES
		MINIMIZE DATATAG NO OMITTAG YES RANK NO SHORTTAG
		YES LINK SIMPLE NO IMPLICIT NO EXPLICIT NO
	35	LINK SIMPLE NO IMPLICIT NO EXPLICIT NO OTHER CONCUR NO SUBDOC NO FORMAL YES
		APPINFO NONE>
	40	legislation</th
		[
		</td
		DTD for Scantext/Abha Legislation - (C) Turn-Key Systems 1997
	45	DTD for Scanext/Abia Legislation - (C) Turn-Key Systems 1997
	40	History:
		1997-10-13: fix hist at beginning of regs

366274US

-84-

1997-10-07: restore <target> tag 1997-10-02: enhanced support for regulations (hist, unconv etc)

_	>
5	useful characters such as — ENTITY % ISOpub public "ISO 8879-1986//ENTITIES Publishing//EN" %ISOpub;
10	PARAMETER ENTITIES USED TO SIMPLIFY DTD MARKUP entity % major<br "schedule intcon article annex clause chapter part division subdivn section subsec reg subreg"
15	major levels >
	< !entity % minor "defn para subpar1 subpar2 subpar3 subpar4 point" minor levels>
20	entity % secreg "section reg"<br used where either sections or regs are appropriate>
25	entity % level "%major; %minor;"<br all levels>
25	entity % refs "term l.ref h.ref"<br references which can be found in normal text>
30	entity % raw "(rawtext rawtable unconverted)*"<br material such as forms which remains as raw text>
	entity % effect "sc"<br typographical effects (more to be added later)>
35	entity % text "(%refs; %effect; #PCDATA)*"<br normal text (including refs defined above)>
40	entity % hnote "hist note"<br hist and note are temporarily interchangeable>
40	entity % body "(p+ repealed), (%hnote;)*"<br body of a legislative element>
45	entity % lev.id "((label, desc?) (desc, label?))"<br reversible level id>
	MASTER ELEMENT

366274US

HOT DESERT DESERT

IN:\LIBCC|01206US.DOC:HAD

```
-85-
```

```
<!element legislation -- (act | regulations)+
           -- Acts and Regs are currently supported -->
      < !-- DEFINITIONS OF ACTS AND CONSTITUENT ELEMENTS -->
 5
      <!element act
                          -- (desc, (%hnote; | %raw;)*,
                 longtitle, preamble?,
                 (chapter + | part + | section +),
                 schedule*, hist*)>
      <!element longtitle -- (#PCDATA)>
10
      <!element preamble -- (p+) +(para)>
      <!element regulations -- (desc, (%hnote; | %raw;)*,
                 (chapter + | part + | reg +),
                 schedule*, hist*)>
15
      <!-- MAJOR LEVELS -->
      <!element chapter -- (label, desc, (%hnote;)*,
                 (((\% \text{secreg};)^*, \text{part}^*) | \text{article}+)) >
      <!element part -- (label?, desc, hist*,
20
                (((%secreg;)*, division*) | (article+ | clause+)))>
      <!element division - - (label?, desc, (p | %hnote;)*,
                (((\% \text{secreg};)^*, \text{subdivn}^*) | \text{clause}+)) >
      <!element subdivn - - (label?, desc, (%hnote;)*,
                ((\% \text{secreg};) + | \text{clause} +)) >
25
      <!element section -- (%lev.id;,
                ((subsec+, (modules | module+)?) | repealed))>
      <!element subsec -- (%lev.id;,
                ((p, (p | note)*, hist*) | (repealed, note*, hist*)))>
      <!element modules -- (%lev.id;,
30
                module+)>
      <!element module -- (%lev.id;,
                (submod + | repealed)) >
      <!element submod -- (%lev.id;,
                ((p, (p | %hnote; | method | tabloid)*) | (repealed, (%hnote;)*)))>
35
                      - - (label?, desc, hist?,
      <!element reg
                 (subreg + | repealed)) >
      <!element subreg -- (label, desc?, hist?,
                 ((p, (p | note)*, hist*) | (repealed, note*, hist*)))>
40
      < !-- SCHEDULES, CONVENTIONS etc -->
      < !element schedule - - (label?, desc?, hist*,
                 (chapter + | part + | section + | item + | p + | tabloid + | intcon)?,
                 %raw;)>
45
      <!element intcon -- (desc, preamble,
                 (part + | division + | subdivn + | article +), annex*)>
      <!element annex -- (label?, desc, p*,
                 (part* | division* | clause* | para*))>
```

366274US

```
-86-
```

```
< !element article - - (label, desc, p*,
                (division* | clause* | para*))>
      <!element clause -- (((label, desc?) | (desc, label)), p+)>
      <!element item -- (label?, desc?, %body;)>
 5
      < !-- DEFINITIONS AND MINOR LEVELS -->
      <!element defn -- (%body;)>
      <!element note -- (label?, p+)>
     <!element hist -- (label?, (p+ | %raw;))>
10
     <!element point -- (p+)>
      <!element para -- (label?, %body;)>
      < !element subpar1 -- (label?, %body;)>
     <!element subpar2 -- (label?, %body;)>
15
      <!element subpar3 - - (label?, %body;)>
      <!element subpar4 - - (label?, %body;)>
      <!element method --(\%lev.id;, (p | \%hnote; | step)+)>
20
     <!element step -- (label, %body;)>
      < !-- COMMON CONSTITUENT ELEMENTS -->
     <!element label -- (%text;)
          -- chapter number, section number, etc. -->
25
      <!element desc - - (%text;)
          -- chapter name, section name, etc. -->
      <!element term - - (%text;)
          -- defined term -->
     <!element repealed - o EMPTY
30
          -- indicates that the enclosing level has been repealed -->
                    - - (%minor | %refs; | %effect | tabloid | amend | target | #PCDATA)*
      <!element p
          -- textual paragraph at any level -->
35
      < !-- UNCONVERTED MATERIAL -->
      < !element unconverted - - CDATA
           -- yet to be converted (eg. complex schedules) -->
      <!element rawtext -- CDATA
          -- unconverted text (eg. forms) -->
40
      <!element rawtable -- CDATA
          -- unconverted tables (eg. amended provisions) -- >
      <!-- CROSS-REFERENCES -->
45
      <!element l.ref -- (%text;) -- legislation ref -->
      <!element h.ref -- (%text;) -- history ref -->
```

366274US

TTITUS TITI

-87-

<!-- AMENDMENT MARKUP --> <!element amend -- (%refs | %effect | quote | #PCDATA)* - amendment = action + text -><!element target -- (#PCDATA) 5 -- target of amendment --> <!element quote -- (label | desc | p | % level | % refs | % effect | #PCDATA)* -- quoted material --> <!-- PSEUDO-TABLES --> <!element tabloid - - (label?, desc?, (head | row)+)> 10 <!element head -- (cell+)> <!element row -- (cell+)> <!element cell - - (#PCDATA|p)*> 15 <!-- EFFECTS --> <!element sc -- (#PCDATA) -- small caps --> <!-- ATTRIBUTE LISTS --> 20 juris (cth | nsw | vic | qld | sa | wa | tas | act | nt | imp) <!attlist act #REQUIRED -- jurisdiction year CDATA #REQUIRED -- year assented number CDATA #REQUIRED -- act number reps CDATA #IMPLIED -- 2nd reading (HR) --25 senate CDATA #IMPLIED -- 2nd reading (Sen) -assent CDATA #IMPLIED -- assent date cdate CDATA #IMPLIED -- commencement --> < attlist regulations juris (cth nsw vic qld sa wa tas act nt imp) #REQUIRED -- jurisdiction 30 year CDATA #REQUIRED -- year assented number CDATA #REQUIRED -- act number reps CDATA #IMPLIED -- 2nd reading (HR) -senate CDATA #IMPLIED -- 2nd reading (Sen) -notified CDATA #IMPLIED -- notification date --35 cdate CDATA #IMPLIED -- commencement --> <!attlist schedule id ID #IMPLIED -- legislation id -cdate CDATA #IMPLIED -- commencement --refsec CDATA #IMPLIED -- referring section --> < !attlist chapter id ID #IMPLIED -- legislation id --40 cdate CDATA #IMPLIED -- commencement --> id ID #IMPLIED -- legislation id --< !attlist part cdate CDATA #IMPLIED -- commencement --> <!attlist division id ID #IMPLIED -- legislation id -cdate CDATA #IMPLIED -- commencement 45 --> <!attlist subdivn id ID #IMPLIED -- legislation id -cdate CDATA #IMPLIED -- commencement --> <!attlist section id ID #IMPLIED -- legislation id --

[N:\LIBCC]01206US.DOC:AD

366274US

-88-

	cdate CDATA #IMPLIED commencement	>
	attlist subsec id ID #IMPLIED legislation id</th <th></th>	
	cdate CDATA #IMPLIED commencement	>
	< attlist reg id ID #IMPLIED legislation id	
5	cdate CDATA #IMPLIED commencement	>
	< attlist subreg id ID #IMPLIED legislation id	
	cdate CDATA #IMPLIED commencement	>
	<pre><!--attlist l.ref ref IDREF #IMPLIED legislation idref</pre--></pre>	>
	attlist term id ID #IMPLIED term id	
10]>	

366274US

We claim:

1. A computer-implemented system for publishing an electronic publication using text-based data, comprising:

- a plurality of predefined portions of text-based data with each predefined portion being stored;
- at least one predefined portion being modified and stored;
- a plurality of linking means of a markup language, each predefined portion of said text-based data and said at least one modified predefined portion of text-based data being encoded with at least one linking means; and
- a plurality of attributes, each attribute being a point on an axis of a multidimensional space for organising said plurality of predefined portions and said at least one modified predefined portion of said text-based data.

2. The system according to claim 1, comprising means for 15 searching within the system.

3. The system according to claim 2, wherein said searching means uses one or more attributes.

4. The system according to claim 2, wherein said searching means uses any predefined portion, any modification of 20 a predefined portion, or any word or phrase within such predefined portion or such modification.

5. The system according to claim 1, further comprising means for searching at least one of said text-based predefined portions of said data using said plurality of 25 attributes, wherein said plurality of attributes are coupled to each of said predefined portions by said respective linking means, and for retrieving one or more of said predefined portions using said plurality of attributes to define a point in said multidimensional space.

6. The system according to claim 1, wherein said markup language is Standard Generalised Markup Language (SGML) or eXtensible Markup Language (XML).

7. The system according to claim 6, wherein said textbased data is encoded using one or more Document Type 35 Definitions (DTD) or Style Sheet Mechanisms (SSM).

8. The system according to claim 1, wherein said linking means comprises any piece of information additional to the body of the text-based data.

9. The system according to claim 8, wherein said linking 40 means is a code or markup that allows departure and destination points to be created between portions of said text-based data.

10. The system according to claim 1, wherein said at least one linking means comprises an identification code for said 45 Language (SGML) or eXtensible Markup Language (XML). respective predefined portion.

11. The system according to claim 1, wherein a first database comprises said plurality of predefined portions of text-based data.

database comprises said plurality of attributes for managing said first database.

13. The system according to claim 1, wherein said predefined portions are encoded with one or more attributes.

14. The system according to claim 1, wherein said respec- 55 tive predefined portion is changed by performing one of the group consisting of adding at least one attribute to said respective predefined portion, deleting at least one attribute from said respective predefined portion, and modifying at least one of the attributes of said respective predefined 60 portion.

15. The system according to claim 1, wherein said respective predefined portion is changed by performing one of the group consisting of adding data to said respective predefined portion, deleting data from said respective predefined 65 portion, and modifying data of said respective predefined portion.

16. The system according to claim 1, wherein said textbased data comprises legislation.

17. The system according to claim 16, wherein each of said plurality of predefined portions of said text-based data is a respective provision of said legislation.

18. The system according to claim 17, wherein said provision is a section or schedule of an Act, or a regulation or schedule of a Regulation(s).

19. The system according to claim 1, wherein each predefined portion is a block of said text-based data, said block being larger than a single word and less than an entire document of said text-based data.

20. A computer readable recording medium for publishing an electronic publication using text-based data, comprising:

- a plurality of predefined portions of text-based data with each predefined portion being stored;
 - at least one predefined portion being modified and stored; and
 - a plurality of linking means of a markup language, each predefined portion of said text-based data and said at least one modified predefined portion of text-based data being encoded with at least one linking means; and
 - a plurality of attributes, each attribute being a point on an axis of a multidimensional space for organising said plurality of predefined portions and said at least one modified predefined portion of said text-based data.

21. The recording medium according to claim 20, wherein means for searching can be used to search the recording medium.

22. The recording medium according to claim 21, wherein 30 said searching means uses one or more attributes.

23. The recording medium according to claim 21, wherein said searching means uses any predefined portion, any modification of a predefined portion, or any word or phrase within such predefined portion or such modification.

24. The recording medium according to claim 20, further comprising means for searching at least one of said predefined portions of said text-based data uses said plurality of attributes, wherein said plurality of attributes are coupled to each of said predefined portions by said respective linking means, and for retrieving one or more of said predefined portions using said plurality of attributes to define a point in said multidimensional space.

25. The recording medium according to claim 20, wherein said markup language is Standard Generalised Markup

26. The recording medium according to claim 25, wherein said text-based data is encoded using one or more Document Type Definitions (DTD) or Style Sheet Mechanisms (SSM).

27. The recording medium according to claim 20, wherein 12. The system according to claim 11, wherein a second 50 said linking means comprises any piece of information additional to the body of the text-based data.

> 28. The recording medium according to claim 27, wherein said linking means is a code or markup that allows departure and destination points to be created between portions of said text-based data.

> 29. The recording medium according to claim 20, wherein said at least one linking means comprises an identification code for said respective predefined portion.

> **30**. The recording medium according to claim **20**, wherein a first database comprises said plurality of predefined portions of said text-based data.

> 31. The recording medium according to claim 30, wherein a second database comprises said plurality of attributes for managing said first database.

> 32. The recording medium according to claim 20, wherein said predefined portions are encoded with one or more attributes.

15

25

33. The recording medium according to claim 20, wherein said respective predefined portion is changed by performing one of the group consisting of adding at least one attribute to said respective predefined portion, deleting at least one attribute from said respective predefined portion, and modifying at least one of the attributes of said respective predefined portion.

34. The recording medium according to claim 20, wherein said respective predefined portion is changed by performing one of the group consisting of adding data to said respective 10 predefined portion, deleting data from said respective predefined portion, and modifying data of said respective predefined portion.

35. The recording medium according to claim 20, wherein said text-based data comprises legislation.

36. The recording medium according to claim 35, wherein each of said plurality of predefined portions of said textbased data is a respective provision of said legislation.

37. The recording medium according to claim 36, wherein said provision is a section or schedule of an Act, or a 20 least one linking means comprises an identification code for regulation or schedule of a Regulation(s).

38. The recording medium according to claim 20, wherein said recording medium is made from one of the group consisting of magnetic media, optical media, and magnetooptical media.

39. The recording medium according to claim **20**, wherein each predefined portion is a block of said text-based data, said block being larger than a single word and less than an entire document of said text-based data.

40. A computer-implemented method for publishing an 30 electronic publication using text-based data, comprising the steps of:

providing a plurality of predefined portions of text-based data with each predefined portion being stored;

- encoding each predefined portion of said text-based data 35 with at least one linking means of a markup language;
- providing at least one predefined portion being modified and stored;
- point on an axis of a multidimensional space for organising said plurality of predefined portions and said at least one modified predefined portion of said textbased data.

41. The method according to claim 40, comprising the $_{45}$ step of searching said text-based data.

42. The method according to claim 41, wherein said searching step uses one or more attributes.

43. The method according to claim 41, wherein said searching step uses any predefined portion, any modification 50 of a predefined portion, or any word or phrase within such predefined portion or such modification.

44. The method according to claim 40, further comprising the step of searching at least one of said predefined portions of said text-based data using said plurality of attributes, wherein said plurality of attributes are coupled to each of said predefined portions by said respective linking means, and for retrieving one or more of said predefined portions using said plurality of attributes to define a point in said multidimensional space.

45. The method according to claim 40, wherein said markup language is Standard Generalised Markup Language (SGML) or eXtensible Markup Language (XML).

46. The method according to claim 45, wherein said text-based data is encoded using one or more Document Type Definitions (DTD) or Style Sheet Mechanisms (SSM).

47. The method according to claim 40, wherein said linking means comprises any piece of information additional to the body of the text-based data.

48. The method according to claim 47 wherein said linking means is a code or markup that allows departure and destination points to be created between portions of said text-based data.

49. The method according to claim 40, wherein said at said respective predefined portion.

50. The method according to claim 40, wherein a first database comprises said plurality of predefined portions of said text-based data.

51. The method according to claim 50, wherein a second database comprises said plurality of attributes for managing said first database.

52. The method according to claim 40, wherein said predefined portions are encoded with one or more attributes.

53. The method according to claim 40, wherein said respective predefined portion is changed by performing one of the group consisting of adding at least one attribute to said respective predefined portion, deleting at least one attribute from said respective predefined portion, and modifying at least one of the attributes of said respective predefined portion.

54. The method according to claim 40, wherein said respective predefined portion is changed by performing one of the group consisting of adding data to said respective providing a plurality of attributes, each attribute being a 40 predefined portion, deleting data from said respective predefined portion, and modifying data of said respective predefined portion.

> 55. The method according to claim 40, wherein said text-based data comprises legislation.

> 56. The method according to claim 55, wherein each of said plurality of predefined portions of text-based data is a respective provision of said legislation.

> 57. The method according to claim 56, wherein said provision is a section or schedule of an Act, or a regulation or schedule of a Regulation(s).

> 58. The method according to claim 40, wherein each predefined portion is a block of said text-based data, said block being larger than a single word and less than an entire document of said text-based data.