

ALVERSON, TAYLOR, MORTENSEN & SANDERS
LAWYERS
7401 WEST CHARLESTON BOULEVARD
LAS VEGAS, NEVADA 89117-1401
(702) 384-7000

**ALVERSON, TAYLOR,
MORTENSEN & SANDERS**
KURT R. BONDS, ESQ.
Nevada Bar No. 6228
ADAM R. KNECHT, ESQ.
Nevada Bar No. 13166
7401 W. Charleston Boulevard
Las Vegas, NV 89117
(702) 384-7000
efile@alversontaylor.com
Attorneys for Plaintiff

UNITED STATES DISTRICT COURT

DISTRICT OF NEVADA

* * *

VOIP-PAL.COM, INC, a Nevada corporation,

Plaintiff,

v.

APPLE, INC, a California corporation,

Defendants.

CASE NO.:

CHART 4

**ASSERTED CLAIMS AND
INFRINGEMENT CONDITIONS**

CHART 4

**CHART SUPPORTING ASSERTED CLAIMS AND INFRINGEMENT CONTENTIONS
CONCERNING U.S. PATENT NO. 9,179,005**

Apple Inc. (“Apple”) manufacturers devices related to and supports a calling platform (“Apple Wi-Fi Calling”) that includes Apple desktop computers, laptops, tablets and mobile devices, software applications running on such devices and servers operated by wireless carriers that allows calls to be placed over Wi-Fi networks. Apple induces the infringement of certain claims of U.S. Patent 9,179,005 (“the ‘005 patent”) as illustrated in the chart below.


Apple Wi-Fi Calling allows an Apple device to initiate a call between a caller, or a first participant, and a callee, or a second participant, using a carrier assisted voice over IP (“VoIP”) system and the callee or second participant may be a subscriber of the carrier or a non-subscriber.

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28

A profile that includes attributes is used as part of the process that classifies a call.


U.S. Patent No. 8,542,815	
Claim	Accused Device/Instrumentality
<p>1. [1p] A process for producing a routing message for routing communications between a caller and a callee in a communication system, the process comprising:</p>	<p>Apple Wi-Fi Calling produces a routing message for routing communications between a caller and a callee in a communication system.</p> <p>Apple supports Wi-Fi Calling on desktop, tablet and mobile devices including iPhone and Apple Watch devices.</p> <p style="text-align: center;">Make a call with Wi-Fi Calling</p> <p style="text-align: center;">With Wi-Fi Calling, you can place a phone call in an area with little or no cellular coverage. Learn how to make a voice call using Wi-Fi Calling.</p> <div style="text-align: center;">  </div> <p>Apple Wi-Fi Calling is a carrier-assisted system that allows Mac desktop computers, iPads, iPhones and Apple Watches connected to a Wi-Fi network to place calls to other users.</p> <p>Apple Wi-Fi Calling operates in the United States in conjunction with AT&T, Sprint and T-Mobile (“carrier”) systems.</p>

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28

U.S. Patent No. 8,542,815	
Claim	Accused Device/Instrumentality
	<p>Place a Wi-Fi call from another device (T-Mobile, Sprint, and AT&T)</p> <ul style="list-style-type: none"> • If you're in the United States and use T-Mobile, you can place a Wi-Fi call from your iPad or iPod touch with iOS 9 or later. • If you're in the United States and use Sprint, you can place a Wi-Fi call from your iPad or iPod touch with iOS 9.1 or later. • If you're in the United States and use AT&T, you can place a Wi-Fi call from your iPad or iPod touch with iOS 9.2. <p>You can also make Wi-Fi calls with Apple Watch with watchOS 2, or Mac with OS X El Capitan. When you place the call, your iPhone could be right next to you or far away—it could even be off.</p>
<p>[1a] using a caller identifier associated with the caller to locate a caller dialing profile comprising a plurality of calling attributes associated with the caller;</p>	<p>Apple Wi-Fi Calling uses a caller identifier associated with the caller to locate a caller dialing profile comprising a plurality of calling attributes associated with the caller.</p> <p>The caller identifier includes a phone number associated with the caller. A call is initiated by the Apple device beginning with the establishment of communication between the device and a server operated by the carrier. A caller dialing profile including calling attributes includes information used in the classification of a call, such as settings stored on the Apple device, information stored on the carrier servers, and/or information obtained regarding the connection of the caller device to the network.</p> 
<p>[1b] when at least one of said calling attributes and at least a</p>	<p>Apple Wi-Fi Calling determines if at least one of the calling attributes and at least a portion of a callee identifier associated with the callee meet private network classification criteria.</p>


1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28

U.S. Patent No. 8,542,815



Claim	Accused Device/Instrumentality
<p>portion of a callee identifier associated with the callee meet private network classification criteria,</p>	<p>Apple Wi-Fi Calling allows calls to be made using the carrier’s private network and over a public network such as the PSTN. The callee identifier includes a phone number associated with the callee. Private network classification criteria represents routing calls over the carrier’s private network. Calling attributes are used to establish a private network classification criteria.</p> <p>One example of calling attributes being used to establish private network classification criteria is the use of caller related information to interpret the callee identifier. The callee identifier may need to be interpreted according to the location from which the caller is registered and/or the location from which the caller is currently located, for example to handle international, national and local dialing patterns. Also, abbreviated dialing patterns such as 311, 511 and 811 are handled according to a local calling area. An “Emergency Address” is needed in the case of 911 calls that are handled using Apple Wi-Fi Calling.</p> <p>* When cellular service is available, your iPhone uses it for emergency calls. If you turned on Wi-Fi Calling and cellular service isn’t available, emergency calls might use Wi-Fi calling. Emergency calls might send your device’s location information to help emergency workers find you, regardless of whether you turn on Location Services.</p>  <p>The Apple Wi-Fi Calling setup screen indicates that “For short code calls, the city will be sent for call routing purpose.”</p>

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28

U.S. Patent No. 8,542,815

Claim	Accused Device/Instrumentality
	 <p>Another example of calling attributes being used to establish private network classification criteria is the use of caller account status information. If the account of the caller is active and has not blocked communication with the callee and the callee is a carrier subscriber, then the call can be made using the carrier's private network. The caller account could be set up to block certain outgoing calls, such as international calls or toll destinations. The caller account could also be set up to block calls to specific numbers.</p> <p>Another example of calling attributes being used to establish private network classification criteria is determining if the caller account has sufficient authorization to process a charge associated with the communication. If a call involves a charge and the caller account can process the charge, and the callee is a carrier subscriber, then the call can be made using the carrier's private network.</p>
<p>[1c] producing a private network routing message for receipt by a call controller, said private network routing message identifying an address, on the private network, associated with the callee; and</p>	<p>Apple Wi-Fi Calling produces a private network routing message for receipt by a call controller which identifies an address on the private network associated with the callee.</p> <p>The carrier operated controller routes the call using a routing message to its own subscriber over its private network.</p>
<p>[1d] when at least one of said calling attributes and at least a portion of said</p>	<p>Apple Wi-Fi Calling determines if at least one of the calling attributes and at least a portion of the callee identifier meet public network classification criteria.</p> <p>Apple Wi-Fi Calling allows calls to be made using the carrier's private</p>

U.S. Patent No. 8,542,815

Claim	Accused Device/Instrumentality
callee identifier meet a public network classification criterion,	<p>network and over a public network such as the PSTN. Public network classification criteria represents routing calls over a public network such as the PSTN. Calling attributes are used to establish a public network classification criteria.</p> <p>One example of calling attributes being used to establish public network classification criteria is the use of caller related information to interpret the callee identifier. The callee identifier may need to be interpreted according to the location from which the caller is registered and/or the location from which the caller is currently located, for example to handle international, national and local dialing patterns. Also, abbreviated dialing patterns such as 311, 511 and 811 are handled according to a local calling area. An “Emergency Address” is needed in the case of 911 calls that are handled using Apple Wi-Fi Calling.</p> <p>* When cellular service is available, your iPhone uses it for emergency calls. If you turned on Wi-Fi Calling and cellular service isn't available, emergency calls might use Wi-Fi calling. Emergency calls might send your device location information to help emergency workers find you, regardless of whether you turn on Location Services.</p>  <p>The Apple Wi-Fi Calling setup screen indicates that “For short code calls, the city will be sent for call routing purpose.”</p> 

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28

U.S. Patent No. 8,542,815	
Claim	Accused Device/Instrumentality
	<p>Another example of calling attributes being used to establish public network classification criteria is the use of caller account status information. If the account of the caller is active and has not blocked communication with the callee and the callee is not a carrier subscriber, then the call must be made using a public network such as the PSTN. The caller account could be set up to block certain outgoing calls, such as international calls or toll destinations. The caller account could also be set up to block calls to specific numbers.</p> <p>Another example of calling attributes being used to establish public network classification criteria is determining if the caller account has sufficient authorization to process a charge associated with the communication. If a call involves a charge and the caller account can process the charge, and the callee is not a carrier subscriber, then the call must be made using a public network such as the PSTN.</p>
<p>[1e] producing a public network routing message for receipt by the call controller, said public network routing message identifying a gateway to the public network.</p>	<p>Apple Wi-Fi Calling produces a public network routing message for receipt by a call controller which identifies a gateway to the public network.</p> <p>If a call is made over a public network, the carrier operated controller routes the call using a routing message to a gateway associated with a public network such as the PSTN.</p>
<p>24. The process of claim 1, further comprising causing the private network routing message or the public network routing message to be communicated to a call controller to effect routing of the call.</p>	<p>Apple Wi-Fi Calling causes the private network routing message or the public network routing message to be communicated to a call controller to effect routing of the call.</p> <p>Apple Wi-Fi Calling uses a call routing controller apparatus that includes the Apple device and/or carrier operated equipment.</p>
<p>25. A non-</p>	<p>Apple Wi-Fi Calling includes a non-transitory computer readable medium</p>

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28

U.S. Patent No. 8,542,815	
Claim	Accused Device/Instrumentality
transitory computer readable medium encoded with codes for directing a processor to execute the method of claim 1.	<p>encoded with codes for directing a processor to execute the method of claim 1.</p> <p>Apple Wi-Fi Calling uses processors with instructions in the Apple device and/or carrier operated equipment.</p> <p>See claim elements [1p], [1a], [1b], [1c], [1d] and [1e].</p>
26. [26p] A call routing controller apparatus for producing a routing message for routing communications between a caller and a callee in a communication system, the apparatus comprising:	<p>Apple Wi-Fi Calling include a call routing controller apparatus for producing a routing message for routing communications between a caller and a callee in a communication system.</p> <p>Apple Wi-Fi Calling uses a call routing controller apparatus that includes the Apple device and/or carrier operated equipment.</p> <p>See claim element [1p].</p>
[26a] at least one processor operably configured to:	<p>Apple Wi-Fi Calling includes at least one processor.</p> <p>Apple Wi-Fi Calling uses processors with instruction in the Apple device and/or carrier operated equipment.</p>
[26b] use a caller identifier associated with the caller to locate a caller dialing profile comprising a plurality of calling attributes associated with the caller;	See claim element [1a].
[26c] when at	See claim element [1b].

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28

U.S. Patent No. 8,542,815	
Claim	Accused Device/Instrumentality
<p>least one of said calling attributes and at least a portion of a callee identifier associated with the callee meet private network classification criteria,</p>	
<p>[26d] produce a private network routing message for receipt by a call controller, said private network routing message identifying an address, on the private network, associated with the callee; and</p>	<p>See claim element [1c].</p>
<p>[26e] when at least one of said calling attributes and at least a portion of said callee identifier meet a public network classification criterion,</p>	<p>See claim element [1d].</p>
<p>[26f] produce a public network routing message for receipt by the call controller, said public network routing message identifying a</p>	<p>See claim element [1e].</p>

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28

U.S. Patent No. 8,542,815	
Claim	Accused Device/Instrumentality
gateway to the public network.	
49. The apparatus of claim 26, wherein said at least one processor is further operably configured to cause the private network routing message or the public network routing message to be communicated to a call controller to effect routing of the call.	<p>Apple Wi-Fi Calling causes the private network routing message or the public network routing message to be communicated to a call controller to effect routing of the call.</p> <p>Apple Wi-Fi Calling uses a call controller that includes the Apple device and/or carrier operated equipment.</p>
50. [50p] A call routing controller apparatus for producing a routing message for routing communications between a caller and a callee in a communication system, the apparatus comprising:	<p>Apple Wi-Fi Calling includes a call routing controller apparatus for producing a routing message for routing communications between a caller and a callee in a communication system.</p> <p>Apple Wi-Fi Calling uses a call routing controller apparatus that includes the Apple device and/or carrier operated equipment.</p> <p>See claim element [1p].</p>
[50a] means for using a caller identifier associated with the caller to locate a caller dialing profile comprising a	See claim element [1a].

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28


U.S. Patent No. 8,542,815	
Claim	Accused Device/Instrumentality
plurality of calling attributes associated with the caller; and	
[50b] means for, when at least one of said calling attributes and at least a portion of a callee identifier associated with the callee meet private network classification criteria,	See claim element [1b].
[50c] producing a private network routing message for receipt by a call controller, said private network routing message identifying an address, on the private network, associated with the callee; and	See claim element [1c].
[50d] means for, when at least one of said calling attributes and at least a portion of said callee identifier meet a public network classification criterion,	See claim element [1d].
[50e] producing a public network routing message	See claim element [1e].

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28


U.S. Patent No. 8,542,815	
Claim	Accused Device/Instrumentality
for receipt by the call controller, said public network routing message identifying a gateway to the public network.	
73. The apparatus of claim 50, further comprising means for causing the private network routing message or the public network routing message to be communicated to a call controller to effect routing of the call.	See claim element [49].
74. [74p] A method of routing communications in a packet switched network in which a first participant identifier is associated with a first participant and a second participant identifier is associated with a second participant in a communication, the method	Apple Wi-Fi Calling routes communications in a packet switched network in which a first participant identifier is associated with a first participant and a second participant identifier is associated with a second participant in a communication. Apple supports Wi-Fi Calling on desktop, tablet and mobile devices including iPhone and Apple Watch devices.

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28

U.S. Patent No. 8,542,815



Claim	Accused Device/Instrumentality
comprising:	<p data-bbox="565 304 1039 346">Make a call with Wi-Fi Calling</p> <p data-bbox="565 367 1396 430">With Wi-Fi Calling, you can place a phone call in an area with little or no cellular coverage. Learn how to make a voice call using Wi-Fi Calling.</p>  <p data-bbox="552 934 1485 1039">Apple Wi-Fi Calling is a carrier-assisted system that allows Mac desktop computers, iPads, iPhones and Apple Watches connected to a Wi-Fi network to place calls to other users.</p> <p data-bbox="552 1071 1445 1144">Apple Wi-Fi Calling operates in the United States in conjunction with AT&T, Sprint and T-Mobile (“carrier”) systems.</p> <p data-bbox="560 1186 1047 1333">Place a Wi-Fi call from another device (T-Mobile, Sprint, and AT&T)</p> <ul data-bbox="568 1354 1120 1669" style="list-style-type: none">• If you're in the United States and use T-Mobile, you can place a Wi-Fi call from your iPad or iPod touch with iOS 9 or later.• If you're in the United States and use Sprint, you can place a Wi-Fi call from your iPad or iPod touch with iOS 9.1 or later.• If you're in the United States and use AT&T, you can place a Wi-Fi call from your iPad or iPod touch with iOS 9.2. <p data-bbox="560 1690 1112 1816">You can also make Wi-Fi calls with Apple Watch with watchOS 2, or Mac with OS X El Capitan. When you place the call, your iPhone could be right next to you or far away—it could even be off.</p> <p data-bbox="552 1879 1429 1921">Apple Wi-Fi Calling communicates over a packet switched network.</p>

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28

U.S. Patent No. 8,542,815	
Claim	Accused Device/Instrumentality
	<p>The first participant identifier includes a phone number associated with the first participant. The second participant identifier includes a phone number associated with the second participant.</p>
<p>[74a] after the first participant has accessed the packet switched network to initiate the communication, using the first participant identifier to locate a first participant profile comprising a plurality of attributes associated with the first participant;</p>	<p>Apple Wi-Fi Calling, after the first participant has accessed the packet switched network to initiate the communication, uses the first participant identifier to locate a first participant profile comprising a plurality of attributes associated with the first participant.</p> <p>A call is initiated by the Apple device beginning with the establishment of communication between the device and a server operated by the carrier. A first participant profile including attributes includes information used in the classification of a call, such as settings stored on the Apple device, information stored on the carrier servers, and/or information obtained regarding the connection of the first participant device to the network.</p> 
<p>[74b] when at least one of the first participant attributes and at least a portion of the second participant identifier meet a first network classification criterion,</p>	<p>Apple Wi-Fi Calling determines if at least one of the first participant attributes and at least a portion of the second participant identifier meet a first network classification criterion.</p> <p>Apple Wi-Fi Calling allows calls to be made using the carrier's private network and over a public network such as the PSTN. First network classification criteria represents routing calls over the carrier's private network. First participant attributes are used to establish a first network classification criteria.</p> <p>One example of first participant attributes being used to establish first network classification criteria is the use of first participant related information to interpret the second participant identifier. The second participant identifier may need to be interpreted according to the location from which the first participant is registered and/or the location from which the first participant is currently located, for example to handle international, national and local dialing patterns. Also, abbreviated dialing patterns such as 311, 511 and 811 are handled according to a local calling area. An "Emergency Address" is needed in the case of 911 calls that are</p>

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28

U.S. Patent No. 8,542,815



Claim	Accused Device/Instrumentality
	<p>handled using Apple Wi-Fi Calling.</p> <p>* When cellular service is available, your iPhone uses it for emergency calls. If you turned on Wi-Fi Calling and cellular service isn't available, emergency calls might use Wi-Fi calling. Emergency calls might send your device's location information to help emergency workers find you, regardless of whether you turn on Location Services.</p>  <p>The Apple Wi-Fi Calling setup screen indicates that “For short code calls, the city will be sent for call routing purpose.”</p>  <p>Another example of first participant attributes being used to establish first network classification criteria is the use of first participant account status information. If the account of the first participant is active and has not blocked communication with the second participant and the second participant is a carrier subscriber, then the call can be made using the carrier's private network. The first participant account could be set up to block certain outgoing calls, such as international calls or toll destinations. The first participant account could also be set up to block calls to specific numbers.</p> <p>Another example of first participant attributes being used to establish first network classification criteria is determining if the first participant account</p>

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28

U.S. Patent No. 8,542,815	
Claim	Accused Device/Instrumentality
	has sufficient authorization to process a charge associated with the communication. If a call involves a charge and the first participant account can process the charge, and the second participant is a carrier subscriber, then the call can be made using the carrier's private network.
[74c] producing a first network routing message for receipt by a controller, the first network routing message identifying an address in a first portion of the packet switched network, the address being associated with the second participant, the first portion being controlled by an entity; and	<p>Apple Wi-Fi Calling produces a first network routing message for receipt by a controller which identifies an address, associated with the second participant, in a first portion of the packet switched network, which is controlled by an entity.</p> <p>The carrier operated controller routes the call using a routing message to its own subscriber over its private network</p>
[74d] when at least one of the first participant attributes and at least a portion of the second participant identifier meet a second network classification criterion,	<p>Apple Wi-Fi Calling determines if at least one of the first participant attributes and at least a portion of the second participant identifier meet a second network classification criterion.</p> <p>Apple Wi-Fi Calling allows calls to be made using the carrier's private network and over a public network such as the PSTN. Second network classification criteria represents routing calls over a public network such as the PSTN. First participant attributes are used to establish a second network classification criteria.</p> <p>One example of first participant attributes being used to establish second network classification criteria is the use of first participant related information to interpret the second participant identifier. The second participant identifier may need to be interpreted according to the location from which the first participant is registered and/or the location from which the first participant is currently located, for example to handle international, national and local dialing patterns. Also, abbreviated dialing patterns such as 311, 511 and 811 are handled according to a local calling area. An "Emergency Address" is needed in the case of 911 calls that are handled using AT&T Wi-Fi Calling.</p>

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28

U.S. Patent No. 8,542,815

Claim	Accused Device/Instrumentality
	<p data-bbox="565 336 1510 451">* When cellular service is available, your iPhone uses it for emergency calls. If you turned on Wi-Fi Calling and cellular service isn't available, emergency calls might use Wi-Fi calling. Emergency calls might send your device's location information to help emergency workers find you, regardless of whether you turn on Location Services.</p>  <p data-bbox="548 976 1494 1050">The Apple Wi-Fi Calling setup screen indicates that “For short code calls, the city will be sent for call routing purpose.”</p>  <p data-bbox="548 1459 1502 1785">Another example of first participant attributes being used to establish second network classification criteria is the use of first participant account status information. If the account of the first participant is active and has not blocked communication with the second participant and the second participant is not a carrier subscriber, then the call must be made using a public network such as the PSTN. The first participant account could be set up to block certain outgoing calls, such as international calls or toll destinations. The first participant account could also be set up to block calls to specific numbers.</p> <p data-bbox="548 1827 1502 1932">Another example of first participant attributes being used to establish second network classification criteria is determining if the first participant account has sufficient authorization to process a charge associated with the</p>

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28

U.S. Patent No. 8,542,815	
Claim	Accused Device/Instrumentality
	communication. If a call involves a charge and the first participant account can process the charge, and the second participant is not a carrier subscriber, then the call must be made using a public network such as the PSTN.
[74e] producing a second network routing message for receipt by the controller, the second network routing message identifying an address in a second portion of the packet switched network, the second portion not controlled by the entity.	<p>Apple Wi-Fi Calling produces a second network routing message for receipt by the controller which identifies an address in a second portion of the packet switched network, which is not controlled by the entity.</p> <p>If a call is made over a public network, the carrier operated controller routes the call using a routing message to a gateway associated with a public network such as the PSTN.</p>
75. The method of claim 74, wherein the packet switched network comprises the Internet.	In Apple Wi-Fi Calling the packet switched network includes the Internet.
76. The method of claim 74, wherein the first participant identifier comprises a first participant telephone number or username.	In Apple Wi-Fi Calling the first participant identifier comprises a first participant telephone number or username.
77. The method of claim 74, wherein the	In Apple Wi-Fi Calling the second participant identifier comprises a second participant telephone number or username.

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28

U.S. Patent No. 8,542,815	
Claim	Accused Device/Instrumentality
second participant identifier comprises a second participant telephone number or username.	
78. The method of claim 74, wherein the communication comprises a voice-over-IP communication.	In Apple Wi-Fi Calling the communication comprises a voice-over-IP communication.
79. The method of claim 74, wherein the packet switched network is accessed via an Internet service provider.	In Apple Wi-Fi Calling the packet switched network is accessed via an Internet service provider.
83. The method of claim 74, wherein the first network classification criterion is satisfied when an address associated with the first participant and the address associated with the second participant are both in the first portion of the packet switched	In Apple Wi-Fi Calling the first network classification criterion is satisfied when an address associated with the first participant and the address associated with the second participant are both in the first portion of the packet switched network.

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28

U.S. Patent No. 8,542,815	
Claim	Accused Device/Instrumentality
network.	
84. The method of claim 74, wherein the address in the first portion is accessible through the first participant's Internet service provider.	In Apple Wi-Fi Calling the address in the first portion is accessible through the first participant's Internet service provider.
88. The method of claim 74, wherein the entity is an entity supplying communication services for the first portion.	In Apple Wi-Fi Calling the entity is an entity supplying communication services for the first portion.
89. The method of claim 74, wherein the second network classification criterion is satisfied when access to the second participant requires routing through a portion of the packet switched network operated by a communication service supplier.	In Apple Wi-Fi Calling the second network classification criterion is satisfied when access to the second participant requires routing through a portion of the packet switched network operated by a communication service supplier.
92. The method of claim 74, wherein the address in the	In Apple Wi-Fi Calling the address in the second portion of the packet switched network comprises an address accessed by a communication service supplier.

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28

U.S. Patent No. 8,542,815	
Claim	Accused Device/Instrumentality
second portion of the packet switched network comprises an address accessed by a communication service supplier.	
94. [94p] A system for routing communications in a packet switched network in which a first participant in a communication has an associated first participant identifier and a second participant in the communication has an associated second participant identifier, the system comprising:	Apple Wi-Fi Calling routes communications in a packet switched network in which a first participant in a communication has an associated first participant identifier and a second participant in the communication has an associated second participant identifier. See claim element [74p].
[94a] a controller comprising: a processor operably configured to access a memory, wherein the processor is configured to:	Apple Wi-Fi Calling includes a controller comprising a processor operably configured to access a memory. Apple Wi-Fi Calling uses a controller with processors, memory and instructions that includes the Apple device and/or carrier operated equipment.
[94b] after the	See claim element [74a].

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28

U.S. Patent No. 8,542,815	
Claim	Accused Device/Instrumentality
<p>first participant has accessed the packet switched network to initiate the communication, locate a first participant profile in the memory using the first participant identifier, the first participant profile comprising a plurality of attributes associated with the first participant;</p>	
<p>[94c] produce a first network routing message when at least one of the first participant attributes and at least a portion of the second participant identifier meet a first network classification criterion,</p>	<p>See claim element [74b].</p>
<p>[94d] the first network routing message identifying an address in a first portion of the packet switched network, the</p>	<p>See claim element [74c].</p>

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28

U.S. Patent No. 8,542,815	
Claim	Accused Device/Instrumentality
address being associated with the second participant, the first portion being controlled by an entity; and	
[94e] produce a second network routing message when at least one of the first participant attributes and at least a portion of the second participant identifier meet a second network classification criterion,	See claim element [74d].
[94f] the second network routing message identifying an address in a second portion of the packet switched network, the second portion not controlled by the entity.	See claim element [74e].
95. The system of claim 94, wherein the communication comprises a voice-over-IP communication.	See claim 78.
96. The system	See claim 79.

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28

U.S. Patent No. 8,542,815	
Claim	Accused Device/Instrumentality
of claim 94, wherein the packet switched network is accessed via an Internet service provider.	
98. The system of claim 94, wherein the second network classification criterion is satisfied when access to the second participant requires routing through a portion of the packet switched network operated by a communication service supplier.	See claim 89.
99. [99p] A non-transitory computer readable medium comprising instructions that when executed cause a processor to perform a method of routing communications in a packet switched network in which a first participant	<p>Apple Wi-Fi Calling includes a non-transitory computer readable medium comprising instructions that when executed cause a processor to perform a method of routing communications in a packet switched network in which a first participant identifier is associated with a first participant and a second participant identifier is associated with a second participant in a communication</p> <p>Apple Wi-Fi Calling uses processors with instructions in the Apple device and/or carrier operated equipment.</p> <p>See claim element [74p].</p>

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28

U.S. Patent No. 8,542,815	
Claim	Accused Device/Instrumentality
<p>identifier is associated with a first participant and a second participant identifier is associated with a second participant in a communication, the method comprising:</p>	
<p>[99a] after the first participant has accessed the packet switched network to initiate the communication, using the first participant identifier to locate a first participant profile comprising a plurality of attributes associated with the first participant;</p>	<p>See claim element [74a].</p>
<p>[99b] when at least one of the first participant attributes and at least a portion of the second participant identifier meet a first network classification criterion,</p>	<p>See claim element [74b].</p>

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28

U.S. Patent No. 8,542,815	
Claim	Accused Device/Instrumentality
[99c] producing a first network routing message for receipt by a controller, the first network routing message identifying an address in a first portion of the packet switched network, the address being associated with the second participant, the first portion being controlled by an entity; and	See claim element [74c].
[99d] when at least one of the first participant attributes and at least a portion of the second participant identifier meet a second network classification criterion,	See claim element [74d].
[99e] producing a second network routing message for receipt by the controller, the second network routing message identifying an address in a second portion of the packet switched	See claim element [74e].

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28

U.S. Patent No. 8,542,815	
Claim	Accused Device/Instrumentality
network, the second portion not controlled by the entity.	