

EXHIBIT C



US007535890B2

(12) **United States Patent**
Rojas

(10) **Patent No.:** **US 7,535,890 B2**
(45) **Date of Patent:** **May 19, 2009**

(54) **SYSTEM AND METHOD FOR INSTANT VOIP MESSAGING**

2007/0112925 A1 * 5/2007 Malik 709/206
2007/0174403 A1 * 7/2007 Barry 709/207

(75) Inventor: **Michael J. Rojas**, North Canton, OH (US)

(73) Assignee: **Ayalogic, Inc.**, Akron, OH (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 799 days.

(21) Appl. No.: **10/740,030**

(22) Filed: **Dec. 18, 2003**

(65) **Prior Publication Data**

US 2005/0135333 A1 Jun. 23, 2005

(51) **Int. Cl.**
H04L 12/66 (2006.01)

(52) **U.S. Cl.** **370/352**; 709/206

(58) **Field of Classification Search** 370/354,
370/352

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

6,763,226 B1 * 7/2004 McZeal, Jr. 455/90.2
2003/0087632 A1 * 5/2003 Sagi et al. 455/414
2003/0126207 A1 * 7/2003 Creamer et al. 709/204
2004/0030046 A1 * 2/2004 Schultes et al. 525/71
2004/0122906 A1 * 6/2004 Goodman et al. 709/206
2004/0128356 A1 * 7/2004 Bernstein et al. 709/206
2004/0252679 A1 * 12/2004 Williams et al. 370/356
2005/0053230 A1 * 3/2005 Gierachf 379/406.06
2005/0105697 A1 * 5/2005 Hollowell et al. 379/88.13
2006/0167883 A1 * 7/2006 Boukobza 707/10
2006/0268750 A1 * 11/2006 Weiner 370/260

OTHER PUBLICATIONS

http://www.cisco.com/warp/public/cc/pd/nemnsnsw/callmn/prodlit/cm33_ds.htm; "Data Sheet Cisco CallManager Version 3.3", Nov. 22, 2002.

http://www.cisco.com/en/US/products/hw/switches/ps1925/products_data_sheet_09186a00800a3c3d.html; "Data Sheet Cisco MGX 8000 Series" (date unknown).

<http://www.hsteliann.com/english/?zone=3100-V21P>; "Telephone 3100-V21P", 2003.

<http://www.linuxdevices.com/articles.AT5199947519.html>;

"Device Profile: snom 100 VoIP phone", May 15, 2002.

http://www.pingtel.com/pr_xpressa.jsp; No limits with the advanced industry standard SIP phone; Dec. 8, 2003.

AudioCoded Enabling Technology Products, TPM-1100 VoIP Media Gateway Modules, copyright 2003.

* cited by examiner


Primary Examiner—Creighton Smith

(74) *Attorney, Agent, or Firm*—Scully, Scott, Murphy & Presser, P.C.

(57) **ABSTRACT**

There is provided an instant voice messaging system (and method) for delivering instant messages over a packet-switched network, the system comprising: a client connected to the network, the client selecting one or more recipients, generating an instant voice message therefor, and transmitting the selected recipients and the instant voice message therefor over the network; and a server connected to the network, the server receiving the selected recipients and the instant voice message therefor, and delivering the instant voice message to the selected recipients over the network, the selected recipients being enabled to audibly play the instant voice message.

70 Claims, 9 Drawing Sheets






FIG. 1
(PRIOR ART)




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9

SYSTEM AND METHOD FOR INSTANT VOIP MESSAGING

BACKGROUND OF THE INVENTION

1. Technical Field of the Invention

The present invention generally relates to Internet telephony (IP telephony). More particularly, the present invention is directed to a system and method for enabling local and global instant VoIP messaging over an IP network, such as the Internet, with PSTN support.

2. Description of the Prior Art

Traditional telephony is based on a public switched telephone network (i.e., "PSTN"). In the PSTN, a telephone terminal is electrically connected to a conventional or legacy switch. The telephone terminal and the legacy switch communicate via a proprietary protocol, which may be different depending on the vendor of the legacy switch. Circuit switching provides a communication path (i.e., dedicated circuit) for a telephone call from the telephone terminal to another device over the PSTN, including another telephone terminal. During the telephone call, voice communication takes place over that communication path.

An alternative to the PSTN is Voice over Internet Protocol (i.e., "VoIP"), also known as IP telephony or Internet telephony. In the IP telephony, a VoIP terminal device is connected to a packet-switched network (e.g., Internet) and voice communication from the VoIP terminal device is digitized, packetized and transmitted over the packet-switched network to a destination VoIP terminal device, which reconstructs the packets and audibly plays, stores or otherwise processes the transmission. The VoIP terminal device may be a VoIP telephone or a general-purpose personal computer (PC) enabled for IP telephony. More specifically, the PC is programmed with the software and equipped with audio input/output devices (e.g., a combination of microphone and speaker or a headset) to serve as a VoIP terminal device. The PC so enabled and equipped will herein be referred to as a VoIP terminal device or a VoIP softphone.

FIG. 1 is an illustrative example of a prior art IP telephony system 100. The IP telephony system 100 comprises a packet-switched IP network 102, such as the Internet, which transmits VoIP traffic from and to a plurality of terminal devices 104, 106 and 110. Terminal device 104 is a VoIP softphone that is enabled for IP telephony over the network 102. Terminal device 106 is a VoIP telephone, which is connected to the network 102 via a softswitch 108. The VoIP softswitch 108 is disposed on the packet-switched network (e.g., Internet) 102 between an origination terminal device (such as VoIP softphone 104) and a destination terminal device (such as VoIP telephone 106), and routes packets over the packet-switched IP network 102. The softswitch 108 may also manage and perform administrative functions for the terminal device or devices (e.g., VoIP telephone 106) to which it is connected. Whether the terminal device is a VoIP softphone 104 or a VoIP telephone 106, the terminal device is connected to the IP network 102 via a networking standard such as Ethernet, Bluetooth, IEEE 1394 (also known as "Firewire"), IEEE 802.11 (also known as "WiFi"), or networking over serial communication channels such as the Universal Serial Bus (i.e., "USB"). Data communication over the network then takes place using a connection protocol, e.g., transfer control protocol/Internet protocol (i.e., "TCP/IP").

Further regarding FIG. 1, terminal device 110 is a legacy telephone that is connected to a legacy switch 112 for (circuit-switched) voice communications over the PSTN 116 with other terminal devices. A media gateway 114 may be pro-

vided between the legacy switch 112 and the packet-switched network 102 to enable IP telephony between the legacy telephone 110 and a VoIP terminal device, such as a VoIP softphone 104 or VoIP telephone 106. More specifically, the media gateway 114 converts the audio signal carried over PSTN to packets carried over the packet-switched IP network 102. In addition, a media gateway 118 may be disposed over the PSTN 116 and connected to a softswitch 120 to convert the audio signal from the legacy telephone 110 to packets routed over the IP network 102 via the softswitch 120.

Voice messaging in both the VoIP and PSTN is known. More specifically, the foregoing systems may be provided with a facility to allow users to leave voice messages for recipients, which is a feature that is familiar to anyone who uses a telephone. Conventionally, leaving a voice message involves dialing the recipient's telephone number (often without knowing whether the recipient will answer), waiting for the connection to be established, speaking to an operator or navigating through a menu of options, listening to a greeting message, and recording the message for later pickup by the recipient. In that message, the user must typically identify himself or herself in order for the recipient to return the call.

Instant text messaging is likewise known. More specifically, a user is provided with a client terminal, which is typically a general-purpose PC programmed with instant text messaging software and in data communication over an IP network with an instant text-messaging server. The instant text-messaging server presents the user, via the client terminal, with a list of persons who are currently "online" and ready to receive text messages on their own client terminals. The user then uses the client terminal to select one or more persons to whom the message will be sent and types in a text message. The text message is sent immediately via the text-messaging server to the selected one or more persons and is displayed on their respective client terminals.

However, notwithstanding the foregoing advances in the VoIP/PSTN voice communication and voice/text messaging, there is still a need in the art for providing a system and method for providing instant VoIP messaging over an IP network. More particularly, there is a need in the art for providing local and global instant voice messaging over VoIP with PSTN support.

SUMMARY OF THE INVENTION

The present invention is directed to a system and method for enabling local and global instant VoIP messaging over an IP network, such as the Internet.

According to an embodiment of the present invention, there is provided an instant voice messaging system for delivering instant messages over a packet-switched network, the system comprising: a client connected to the network, the client selecting one or more recipients, generating an instant voice message therefor, and transmitting the selected recipients and the instant voice message therefor over the network; and a server connected to the network, the server receiving the selected recipients and the instant voice message therefor, and delivering the instant voice message to the selected recipients over the network, the selected recipients being enabled to audibly play the instant voice message.

According to another embodiment of the present invention, there is provided an instant voice messaging system for delivering instant messages over a packet-switched network enabling public switched telephone network (PSTN) support, the system comprising: a PSTN telephone connected to the network for providing input audio; a client connected to the network, the client selecting one or more recipients, generat-

3

ing an instant voice message therefor using the input audio provided by the PSTN telephone, and transmitting the selected recipients and the instant voice message therefor over the network; a server connected to the network, the server receiving the selected recipients and the instant voice message therefor, and delivering the instant voice message to the selected recipients over the network, the selected recipients being enabled to audibly play the instant voice message.

According to a further embodiment of the present invention, there is provided an instant voice messaging system for delivering instant messages over a packet-switched network, the system comprising: a voice-over-internet-protocol (VoIP) telephone connected to the network for providing input audio; a client connected to the network, the client selecting one or more recipients, generating an instant voice message therefor using the input audio provided by the VoIP telephone, and transmitting the selected recipients and the instant voice message therefor over the network; a server connected to the network, the server receiving the selected recipients and the instant voice message therefor, and delivering the instant voice message to the selected recipients over the network, the selected recipients being enabled to audibly play the instant voice message.

According to still another embodiment of the present invention, there is provided an instant voice messaging system for delivering instant messages over a plurality of packet-switched networks, the system comprising: a client connected to a local network, the client selecting one or more external recipients connected to an external network outside the local network, generating an instant voice message therefor, and transmitting the selected recipients and the instant voice message therefor over the local network and the external network; and a server connected to the external network, the server receiving the selected recipients and the instant voice message therefor, and delivering the instant voice message to the selected recipients over the external network, the selected recipients being enabled to audibly play the instant voice message.

According to yet another embodiment of the present invention, there is provided an instant voice messaging system for delivering instant messages over a plurality of packet-switched networks enabling public switched telephone network (PSTN) support, the system comprising: a PSTN telephone connected to a local network for providing input audio; a client connected to the local network, the client selecting one or more external recipients connected to an external network outside the local network, generating an instant voice message therefor using the input audio provided by the PSTN telephone, and transmitting the selected recipients and the instant voice message therefor over the local network and the external network; a server connected to the external network, the server receiving the selected recipients and the instant voice message therefor, and delivering the instant voice message to the selected recipients over the external network, the selected recipients being enabled to audibly play the instant voice message.

According to yet a further embodiment of the present invention, there is provided an instant voice messaging system for delivering instant messages over a plurality of packet-switched networks, the system comprising: a voice-over-internet-protocol (VoIP) telephone connected to a local network for providing input audio; a client connected to the local network, the client selecting one or more external recipients connected to an external network outside the local network, generating an instant voice message therefor using the input audio provided by the VoIP telephone, and transmitting the selected recipients and the instant voice message therefor

4

over the local network and the external network; an server connected to the external network, the external server receiving the selected recipients and the instant voice message therefor, and delivering the instant voice message to the selected recipients over the external network, the selected recipients being enabled to audibly play the instant voice message.

According to still a further embodiment of the present invention, there is provided an instant voice messaging system for delivering instant messages over a plurality of packet-switched networks, the system comprising: a client connected to an external network, the client selecting one or more recipients connected to a local network, generating an instant voice message therefor, and transmitting the selected recipients and the instant voice message therefor over the external network; an external server system connected to the external network, the external server system receiving the selected recipients and the instant voice message, and routing the selected recipients and the instant voice message over the external network and the local network; a local server connected to the local network, the local server receiving the selected recipients and the instant voice message therefor, and delivering the instant voice message to the selected recipients over the local network, the selected recipients being enabled to audibly play the instant voice message.

According to an embodiment of the present invention, there is provided a method for instant voice messaging over a packet-switched network, the method comprising: selecting one or more recipients for instant voice messaging at a client; generating an instant voice message for the selected recipients at the client; transmitting the selected recipients and the instant voice message therefor over the network from the client to a server; receiving the selected recipients and the instant voice message therefor at the server; delivering the instant voice message from the server to the selected recipients over the network; and audibly playing the instant voice message at the selected recipients.

According to another embodiment of the present invention, there is provided a method for instant voice messaging over a packet-switched network enabling public switched telephone network (PSTN) support, the method comprising: providing input audio via a PSTN telephone connected over the network; selecting one or more recipients for instant voice messaging at a client; generating an instant voice message using the input audio from the PSTN telephone for the selected recipients at the client; transmitting the selected recipients and the instant voice message therefor over the network from the client to a server; receiving the selected recipients and the instant voice message therefor at the server; delivering the instant voice message from the server to the selected recipients over the network; and audibly playing the instant voice message at the selected recipients.

According to a further embodiment of the present invention, there is provided a method for instant voice messaging over a packet-switched network, the method comprising: providing input audio via a voice-over-internet-protocol (VoIP) telephone connected over the network; selecting one or more recipients for instant voice messaging at a client; generating an instant voice message using the input audio from the VoIP telephone for the selected recipients at the client; transmitting the selected recipients and the instant voice message therefor over the network from the client to a server; receiving the selected recipients and the instant voice message therefor at the server; delivering the instant voice message from the server to the selected recipients over the network; and audibly playing the instant voice message at the selected recipients.

5

According to still another embodiment of the present invention, there is provided a method for instant voice messaging over a plurality of packet-switched networks, the method comprising: selecting one or more external recipients for instant voice messaging at a client connected to a local network, the one or more external recipients connected to an external network outside the local network; generating an instant voice message for the selected external recipients at the client; transmitting the selected external recipients and the instant voice message therefor over the local network and the external network; receiving the selected external recipients and the instant voice message therefor at an external server connected to the external network; delivering the instant voice message to the selected external recipients over the external network; and audibly playing the instant voice message at the selected external recipients.

According to yet another embodiment of the present invention, there is provided a method for instant voice messaging system over a plurality of packet-switched networks enabling public switched telephone network (PSTN) support, the method comprising: providing input audio via a PSTN telephone connected to a local network; selecting one or more external recipients for instant voice messaging at a client, the one or more external recipients connected to an external network outside the local network; generating an instant voice message for the one or more external recipients using the input audio provided by the PSTN telephone; transmitting the selected recipients and the instant voice message therefor over the local network and the external network; receiving the selected recipients and the instant voice message therefor at a server connected to the external network; delivering the instant voice message to the selected recipients from the server over the external network; and audibly playing the instant voice message at the selected recipients.

According to still a further embodiment of the present invention, there is provided a method for instant voice messaging system over a plurality of packet-switched networks, the method comprising: providing input audio via a voice-over-internet-protocol (VoIP) telephone connected to a local network; selecting one or more external recipients for instant voice messaging at a client, the one or more external recipients connected to an external network outside the local network; generating an instant voice message for the one or more external recipients using the input audio provided by the VoIP telephone; transmitting the selected recipients and the instant voice message therefor over the local network and the external network; receiving the selected recipients and the instant voice message therefor at a server connected to the external network; delivering the instant voice message to the selected recipients from the server over the external network; and audibly playing the instant voice message at the selected recipients.

According to yet a further embodiment of the present invention, there is provided a method for instant voice messaging over a plurality of a plurality of packet-switched networks, the method comprising: selecting one or more recipients connected to a local network at a client connected to an external network; generating an instant voice message for the selected recipients at the client; transmitting the selected recipients and the instant voice message therefor over the external network from the client to an external server system; receiving the selected recipients and the instant voice message at the external server system; routing the selected recipients and the instant voice message over the external network and the local network; receiving the selected recipients and the instant voice message therefor at a local server connected to the local network; delivering the instant voice message to

6

the selected recipients over the local network; audibly playing the instant voice message at the selected recipients.

BRIEF DESCRIPTION OF THE DRAWINGS

The objects, features and advantages of the present invention will become apparent to one skilled in the art, in view of the following detailed description taken in combination with the attached drawings, in which:

FIG. 1 illustrates an example of a prior art IP telephony system;

FIG. 2 illustrates an exemplary local IVM system for enabling instant voice messaging according to the present invention;

FIG. 3 illustrates an exemplary IVM client of FIG. 2 for enabling instant voice messaging according to the present invention;

FIG. 4 illustrates an exemplary IVM server of FIG. 2 for enabling instant voice messaging according to the present invention;

FIG. 5 illustrates an exemplary global IVM system comprising a local IVM system and global IVM clients, according to the present invention;

FIG. 6 illustrates an exemplary global IVM server system depicted in FIG. 5, according to the present invention;

FIG. 7 illustrates an exemplary transport server depicted in FIG. 6, according to the present invention;

FIG. 8 illustrates an exemplary directory server depicted in FIG. 6, according to the present invention; and

FIG. 9 illustrates an exemplary global IVM system comprising a plurality of local IVM systems and global IVM clients, according to the present invention.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT OF THE INVENTION

The present invention is directed to a system and method for enabling local and global instant VoIP messaging over an IP network with PSTN support.

FIG. 2 is an exemplary illustration of a local instant voice messaging (IVM) system **200** according to the present invention. The instant voice messaging system **200** comprises a local IVM server **202** that provides the core functionality for enabling instant voice messaging with PSTN support according to the present invention. The architecture of the local IVM server **202** will be described in detail hereinbelow with reference to FIG. 4. According to the exemplary IVM system **200**, the local IVM server **202** is enabled to provide instant voice messaging to one or more IVM clients **206** and **208**, as well support instant voice messaging for PSTN legacy telephones **110**. It is noted that although FIG. 2 depicts one of each IVM client **206**, **208** and legacy telephone **110** for clarity and brevity, the local IVM server **202** is enabled to support a plurality of each of the foregoing IVM clients **206**, **208** and legacy telephone **110**. The local packet-switched IP network **204** interconnects the IVM clients **206**, **208** and the legacy telephone **110** to the local IVM server **202** as well as interconnecting the local IVM server **202** to the local IP network **204**. The network **204** may be a local area network (LAN), a wide area network (WAN), or the like, which supports both wired and wireless devices. The exemplary IVM client **208** is a VoIP softphone, the architecture of which will be described in detail hereinbelow with reference to FIG. 3. A microphone **212** is connected to the IVM client **208** and enables the recording of an instant voice message according to the present invention into an audio file **210** for transmission to the local IVM server **202** over the network **204**. An input device **218**

7

(e.g., a keyboard) is connected to the IVM client **208** to select one or more recipients that are to receive the recorded instant voice message. Although not depicted in FIG. 2, the input device **218** may include a trackball, digitizing pad or mouse, or the like. A display device **216** is connected to the IVM client **208** to display instant voice messages recorded and/or received by a user of the IVM client **208**. An audio device **214**, such as external speaker, is connected to the IVM client **208** to play received instant voice messages. It is noted that the microphone **212**, audio device **214**, display device **216** and input device **218** may form integral parts of the IVM client **208**.

Further with reference to FIG. 2, IVM client **206** is interconnected via the network **204** to the local IVM server **202**. An exemplary IVM client **206** is a VoIP telephone, which comprises a screen display (not shown) capable of displaying instant voice messages recorded and/or received by a user of the IVM client **206** according to the present invention. The VoIP telephone **206** further comprises a handset and/or speakerphone for recording instant voice messages and listening to instant voice messages received at the VoIP telephone **206** according to the present invention. The VoIP telephones which may be implemented to provide instant voice messaging functionality according to the present invention are commercially available from many vendors, including Alcatel™, Lucent™, NEC™ and Cisco™, to name just a few. In addition to the foregoing IVM clients **206**, **208**, the IVM system **200** supports a legacy telephone **110** for instant voice messaging according to the present invention. The legacy telephone **110** is connected to a legacy switch **112**. The legacy switch **112** is further connected to a media gateway **114**. Both the legacy switch **112** and the media gateway **114** interconnect the legacy telephone **110** via the network **204** to the local IVM server **202**, thereby facilitating instant voice messaging according to the present invention. The media gateway **114** may be a gateway that supports trunk pack network control (i.e., "TPNCP") protocol, media gateway control protocol (i.e., "MGCP"), or a media gateway control H.428 protocol (i.e., "MEGACO"). As previously mentioned, the media gateway **114** converts the audio signal carried over PSTN to packets to be transmitted over a packet-switched IP network, such as the local network **204**.

The implementation of the instant voice messaging for IVM client **208** will be described first and will be followed by the implementations for IVM client **206** and legacy telephone **110**, with reference to the local IVM system **200** depicted in FIG. 2. These implementations implement a "record mode" of the instant voice messaging according to the present invention. There will further be described an "intercom mode" of the instant voice messaging according to the present invention. Therefore, in operation of the IVM client **208** according to FIG. 2, the IVM client (IVM softphone) **208** is connected over the network **204** to the IVM server **202**, which as aforementioned enables instant voice messaging functionality over the network **204**. The IVM client **208** displays a list of one or more IVM recipients on its display **216**, provided and stored by the local IVM server **202**, as will be particularly described hereinbelow with reference to FIG. 4. The user operates the IVM client **208** by using the input device **218** to indicate a selection of one or more IVM recipients from the list. The user selection is transmitted to the IVM server **202**. The user selection also generates a start signal to the IVM client **208** that the user is ready to begin instant voice messaging according to the present invention. In response to the start signal, the IVM client (softphone) **208** listens to the input audio device **212** and records the user's speech into a digitized audio file **210** (i.e., instant voice message) stored on the

8

IVM client **208**. The audio file **210** at the IVM client **208** is finalized via a stop signal, which is generated by the user via the input device **218** or a preset time period without speech input via the input audio device **212** on the IVM client **208**. Once the recording of the user's speech is finalized, IVM client **208** generates a send signal indicating that the digitized audio file **210** (instant voice message) is ready to be sent to the selected recipients. The user generates the send signal when the user operates the IVM client **208** via the input device **218**, e.g., pressing a key on a keyboard or clicking a button on a mouse. The IVM client **208** transmits the digitized audio file **210** and the send signal to the local IVM server **202**. In response to the send signal indicating that the instant voice message is ready to be sent, the IVM client **208** sends the recorded audio file **210** destined for the selected one or more recipients via local IVM server **202**. After receiving the audio file **210**, the IVM server **202** thereafter delivers the transmitted instant voice message to the selected one or more recipients via the local IP network **204**. The one or more recipients are enabled to display an indication that the instant voice message has been received and audibly play the instant voice message to an associated user. It should be understood that only the available IVM recipients, currently connected to the IVM server **202**, will receive the instant voice message. It is noted that if a recipient IVM client is not currently connected to the local IVM server **202** (i.e., is unavailable), the IVM server temporarily saves the instant voice message and delivers it to the IVM client when the IVM client connects to the local IVM server **202** (i.e., is available).

There are several embodiments for the operation of the IVM client (VoIP telephone) **206** within the IVM system **200**, according to the present invention. In the first embodiment, the VoIP telephone **206** is a standalone IVM client **206** enabled for instant voice messaging according to the present invention. In the second embodiment, the VoIP telephone **206** operates synchronously either with the IVM client **208** or IVM server **202** to enable instant voice messaging according to the present invention. Thus, in operation according to the first embodiment in FIG. 2, the IVM client (VoIP telephone) **206** is connected over the network **204** to the IVM server **202**, which as aforementioned enables instant voice messaging functionality over the local network **204**. The IVM client **206** displays a list of one or more IVM recipients on its associated display provided and stored by the local IVM server **202**, as will be particularly described hereinbelow with reference to FIG. 4. The user operates the IVM client **206** by using a keypad on the VoIP telephone **206** to indicate a selection of one or more IVM recipients from the list. The VoIP telephone **206** transmits the selection to the IVM server **202**. The user selection also generates a start signal to the IVM client **206** indicating the user is ready to begin instant voice messaging according to the present invention. The user speaks into the handset of the IVM client **206** or a speakerphone on the IVM client **206**. Although not shown in FIG. 2, the VoIP telephone **206** may provide a dedicated storage device, which in response to the start signal records an audio file, similar to the audio file **210** in the IVM client **208**. The audio file is finalized via a stop signal. The stop signal is generated when the user presses a button on the keypad, a preset time period without speech input to the VoIP telephone **206**, or when the user returns the handset to the cradle of the VoIP telephone **206**. Once the recording of the user's speech is complete, a send signal is generated indicating that the instant voice message is ready to be sent to the selected recipients. The user generates the send signal when the user presses a button on the keypad or returns the handset of the VoIP telephone **206** to its cradle (on-hook). In response to the send signal, the IVM client **206**

sends the recorded audio to the local IVM server **202** via the network **204**. The IVM server **202** thereafter delivers the instant voice message to the selected one or more recipients via the IP network **204**. As before, the one or more recipients are enabled to display an indication that the instant voice message has been received and audibly play the instant voice message. As aforementioned, if a recipient IVM client is not currently connected to the local IVM server **202**, the IVM server **202** temporarily saves the instant voice message and delivers it to the IVM client when the IVM client connects to the local IVM server **202**.

In the second embodiment of the IVM client **206** according to FIG. **2**, the VoIP telephone **206** operates synchronously either with the IVM client **208** or the IVM server **202** to enable instant voice messaging according to the present invention. Thus, in operation according to the second embodiment, the IVM client (VoIP telephone) **206** is still connected over the network **204** to the IVM server **202**, which as aforementioned enables instant voice messaging functionality over the local network **204**. However, VoIP telephone **206** cooperates with the IVM client **208** or IVM server **202** to record and send an instant voice message. More specifically, the VoIP telephone **206** is only used as a recording/listening device for recording or listing to instant voice messages, while the IVM client **208** is used for displaying and selecting instant voice message recipients as described hereinabove. In operation, the IVM client **208** displays a list of IVM recipients on the display device **216** provided and stored by the local IVM server **202**. The user operates the IVM client **208** by using the input device **218** on the IVM client **208** to indicate a selection of one or more IVM recipients from the list. The user selection is transmitted to the IVM server **202**. The user selection generates a start signal to the IVM server **202** indicating that the user is ready to begin instant voice messaging according to the present invention. In response to receiving the start signal, the IVM server **202** transmits a ring signal to the VoIP telephone **206**, thereby indicating to the user the IVM system **200** is ready to record an instant voice message. The IVM server **202** also signals the IVM client **208** to generate audio file **210** to record the instant voice message. As the user picks up the handset of the VoIP telephone **206** (off-hook), a connection is established via the network **204** between the local IVM server **202** and the VoIP telephone **206**. Thereafter, the IVM server **202** forwards the user's speech transmitted from VoIP telephone **206** to the IVM client **208** for storage into digitized audio file **210** on the IVM client **208**. The audio file **210** is finalized by returning the handset its cradle (on-hook) or by pressing a designated button on the keypad VoIP telephone **206**, which transmits the stop signal to the IVM server **202** and further from the IVM server **202** to the IVM client **208**. Returning the handset to its cradle preferably generates a send signal to the IVM server **202**, which transmits the signal to the IVM client **208**. The IVM client thereafter transmits the recorded audio file **210** (instant voice message) to IVM server **202** for delivery to the selected one or more IVM recipients. Alternatively, the user may press a key on the keyboard **218** to initiate the send signal. In response to the send signal, the IVM client **206** sends the recorded audio to the local IVM server **202** via the network **204**. The IVM server **202** thereafter delivers the instant voice message to the selected one or more recipients via the IP network **204**. The one or more recipients are enabled to display an indication that the instant voice message has been received and audibly play the instant voice message. If a recipient IVM client is not currently connected to the local IVM server **202**, the IVM

server **202** temporarily saves the instant voice message and delivers it to the IVM client when the IVM client connects to the local IVM server **202**.

In operation of the legacy telephone **110** according to FIG. **2**, the legacy telephone **110** is connected to the local IVM server **202** via media gateway **114** and legacy switch **112**. The legacy telephone **110** cooperates with the IVM client **208** to record and send an instant voice message. More specifically, the legacy telephone **110** is used as a recording/listening device for recording or listing to instant voice messages, while the IVM client **208** is used for displaying and selecting instant voice message recipients as described hereinabove. Thus, in operation the IVM client **208** displays a list of IVM recipients on the display device **216** provided and stored by the local IVM server **202**. The user operates the IVM client **208** by using the input device **218** on the IVM client **208** to indicate a selection of one or more IVM recipients from the list. The user selection is transmitted to the IVM server **202**. The user selection generates a start signal to the IVM server **202** indicating that the user is ready to begin instant voice messaging according to the present invention. In response to receiving the start signal, the IVM server **202** transmits an emulation code to the legacy telephone **110** to ring, thereby indicating to the user the IVM system **200** is ready to record an instant voice message. As the user picks up the handset of the legacy telephone **110** (off-hook), a connection is established via the network **204** between the legacy telephone **110** and the IVM server **202**. Thereafter, the IVM server forwards the user's speech transmitted from the legacy telephone **110** to the IVM client **208** for storage into the digitized audio file **210** (i.e., instant voice message). The audio file on the IVM client **208** is finalized by returning the handset of the legacy telephone **110** to its cradle (on-hook) or by pressing a designated button on the keypad of the legacy telephone **110**, which transmits a stop signal to the IVM server **202** and further to the IVM client **208**. Returning the handset to its cradle also generates a send signal to the IVM server to transmit the recorded audio file (instant voice message) to the selected one or more IVM recipients. The IVM server **202** thereafter delivers the instant voice message to the selected one or more recipients via the IP network **204**. The one or more recipients are enabled to display an indication that the received instant voice message has been received and audibly play the instant voice message. If a recipient IVM client is not currently connected to the local IVM server **202**, the IVM server **202** temporarily saves the instant voice message and delivers it to the IVM client when the IVM client connects to the local IVM server **202**.

Regarding the operational embodiments described with reference to FIG. **2** for recoding and transmitting an instant voice message according to the present invention, the digitized audio file is preferably compressed by applying a compression algorithm before sending the audio file to the one or more selected recipients. The audio file is preferably compressed within the IVM clients **206**, **208** before forwarding the audio file to the IVM server **202** for subsequent delivery to the one or more selected recipients. Alternatively, the compression may be implemented within the IVM server **202** before the audio file is transmitted to the one or more selected recipients. A Lempel-Ziv compression algorithm is preferably used to compress the audio file according to the present invention. It is noted that many suitable compression algorithms are known to persons of skill in the art, including Huffman encoding, audio compression standards promulgated by the Moving Pictures Experts Group ("MPEG"), G.722 wideband speech encoding standard, fractal compression

sion, and wavelet compression. Any of the foregoing compression algorithms may be implemented within the scope of the present invention.

Further regarding the operational embodiments described with reference to FIG. 2 for recoding and transmitting an instant voice message according to the present invention, the digitized audio file (which may or may not be compressed as described above) is further preferably encrypted via an encryption algorithm before transmitting the audio file to the one or more selected recipients. The encryption is preferably implemented within the IVM clients **206**, **208** before forwarding the audio file to the IVM server **202** for subsequent delivery to the one or more selected recipients. Alternatively, the encryption may be implemented within the IVM server **202** before the audio file is transmitted to the one or more selected recipients. An AES (Rijndael) encryption algorithm is preferably used to encrypt the audio file according to the present invention. It is noted that many suitable encryption algorithms are known to persons skilled in the art, including DES, Triple DES, Blowfish, Twofish, Serpent, and the like. Any of the foregoing encryption algorithms may be implemented within the scope of the present invention.

Lastly with reference to FIG. 2, in addition to the “record mode” of instant voice messaging, the instant voice messaging system **200** also supports an “intercom mode” of voice messaging. The “intercom mode” represents real-time instant voice messaging. In the “intercom mode,” instead of creating an audio file **210**, one or more buffers (not shown) of a predetermined size are generated in the IVM client **206**, **208** or local IVM server **202**. The one or more buffers are used to automatically write successive portions of the instant voice message. Once a first buffer is full, i.e., input audio of the predetermined size is written to the buffer, the content of the first buffer is automatically transmitted to the IVM server **202** for transmission to the one or more IVM recipients. A second buffer is meanwhile written with the next successive portion of input audio. Once, the second buffer is full, i.e., input audio of the predetermined size is written to the buffer, the content of the second buffer is transmitted to the IVM server **202** for transmission to the one or more IVM recipients. If the entire instant voice message or a successive portion thereof (such as a last successive portion in the instant voice message) written to either buffer is smaller the predetermined size, then the buffered content of less than the predetermined size is automatically transmitted to the IVM server **202**. The foregoing buffering using the first and second buffers is repeated until the entire instant voice message has been transmitted to the IVM server **202** for transmission to the one or more IVM recipients. It is noted that the invention is not limited to a particular number of buffers. The foregoing buffering and transmission allows a “real-time” instant voice message to be transmitted to the one or more IVM recipients. The “intercom mode” may be designated as a default mode when an IVM recipient is on-line, while the “record mode” may be designated as a default if the IVM recipient is unavailable, i.e., not on-line. The user may easily change the “intercom mode” to the “record mode” on the respective IVM client **206**, **208**. Finally, the audio contents of the buffers may be signal processed (for clarity), encrypted and compressed before transmission, as will be described in more detail hereinbelow with reference to FIG. 3.

FIG. 3, an exemplary illustration of the architecture in the IVM client **208** for enabling instant voice messaging according to the present invention. More specifically, the IVM client **208** comprises a client platform **302** for generating an instant voice message and a messaging system **320** for messaging between the IVM client **208** and the IVM server **202** for

enabling instant voice messaging according to the present invention. The IVM client **208** is a general-purpose programmable computer equipped with a network interface (not shown), such as an Ethernet card, to provide connectivity to the network **204**. It is noted that any suitable networking protocol, not only Ethernet, could be used to connect the IVM client to a network **204** and thus is considered within the scope of the present invention. The client platform **302** comprises a client engine **304**, which controls other components, namely the document handler **306**, file manager **308**, audio file creation **312**, signal processing **314**, encryption/decryption **316**, and compression/decompression **318**. The messaging system **320** and the client engine **304** communicate via standard inter-process communication. The messaging system **320** and client engine **304** also communicate with the IVM server **202** over the network interface via the network **204**. The document handler **306** oversees the retrieving, sending, receiving and storing of one or more documents (or files) attached to instant voice messages from/to the one or more selected IVM recipients that may be communicating with the IVM client **208**. More specifically, when an instant voice message is to be transmitted to the one or more IVM recipients, one or more documents may be attached to the instant voice message to be, stored or displayed by the one or more selected IVM recipients. The file manager accesses a message database **310**, in which both the received and recorded instant voice messages are represented as database records, each record comprising a message identifier and the instant voice message. The file manager **308** services requests from the user to record, delete or retrieve messages to/from the message database **310**. Audio file creation **312** creates an instant voice message as audio file **210**, and is responsible for receiving input speech for the instant voice message from audio input device **212** or via network **204** and storing the input speech into audio file **210**. Signal processing **314** performs noise removal and signal optimization in the audio file **210**. Encryption/decryption **316** provides for respectively encrypting/decrypting of outgoing/incoming audio files (i.e., instant voice messages), and compression/decompression **318** respectively compresses/decompresses the outgoing/incoming audio files.

Further with reference to FIG. 3, the reception of an instant voice message is described as follows. It is assumed that the local IVM server **202** has determined that the IVM client **208** is available to receive an instant voice message by checking the IVM client’s **208** current status, i.e., whether the IVM client **208** is “on-line.” The local IVM server **202** maintains the current status of the IVM clients connected to the local IVM server **202**, i.e., IVM clients **206**, **208**. It is further assumed that an IVM client has transmitted an instant voice message to the IVM client **208**. The local IVM server **202** receives the instant voice message over the local IP network **204** and forwards the instant voice message to the IVM client **208**. Upon receipt at the IVM client **208**, the instant voice message is decrypted at **316**, decompressed at **318**, and stored in the message database **310** using the file manager **308**. Any files attached to the instant voice message are also stored in the message database **310** using the file manager **308**. A visual and/or sound effect is initiated to notify a user of the IVM client **208** that a new instant voice message has been received at the IVM client **208**. At this point in time, the instant voice message and any file attachments are available to the user. The user can select the instant voice message from a listing of available instant voice messages displayed on the IVM client **208** and play the newly received instant voice message. The

13

user may also open any file attachments and move or save the files to a separate location on the client using a drag-and-drop process.

Still further with reference to FIG. 3, the generation and transmission of an instant voice message is described as follows. The user selects the available one or more IVM recipients and initiates the creation of an instant voice message as described above with reference to FIG. 2. The client engine 304 detects the start signal and invokes audio file creation 312 of the audio file 210. The audio file 210 is initialized and captures the audio voice message input by the user. Once the client engine 304 detects a stop signal, the instant voice message is finalized in the audio file 210 via audio file creation 312. The audio file 210 is adjusted for gain, and noise is removed via signal processing 314. The audio file 210 is further compressed at 318 and encrypted at 316. The completion of these processes causes the client engine 304 to inform the user via display 216 that the instant voice message is available to be sent. After the client engine 304 detects the send signal from the user, the instant voice message (audio file 210) is transferred to the local IVM server 202. Before the transmission of the instant voice message (i.e., before the send signal), the user has the option to review the instant voice message, re-record the instant voice message, delete the instant voice, as well as attach one or more files (i.e., documents). The attachment of one or more files is enabled conventionally via a methodology such as "drag-and-drop" and the like, which invokes the document handler 306 to make the appropriate linkages to the one or more files and flags the messaging system 320 that the instant voice message also has the attached one or more files.

FIG. 4, an exemplary illustration of the local IVM server 202 for enabling instant voice messaging according to the present invention. The IVM server 202 is a general-purpose programmable computer equipped with a network interface, such as an Ethernet card, to provide connectivity to a network 204. It is noted that any suitable networking protocol may be implemented to connect the IVM server 202 to a network 204. The IVM server 202 comprises a server communication platform 402, a messaging system 436 and a database 414, thereby enabling instant voice messaging according to the present invention. The server communication platform 402 comprises a server engine 404, client manager 406, station manager 408, gateway manager 410, database manager 412 that accesses database 414, supplemental servers 416 (including particular server subsystems 418-424), as well as a control layer 426 (including non-proprietary server subsystems 428, 430 and proprietary server subsystems 432, 434). The messaging system 436 and the server engine 304 communicate via standard inter-process communication. The messaging system 436 and the server engine are also able to communicate with the IVM clients 206, 208 over the network interface via the network 204. The database 414 stores users (e.g., IVM clients as well as legacy telephone clients) that are known to the IVM server 202 via the database manager 412. The users are represented in the database as records, each record comprising a user name, a password, and a contact list (a list of other users with whom the user wishes to exchange instant voice messages), and other data relating to the user. The database manager 412 services requests to add, update, delete, or retrieve database records to/from the database 414. The password may be stored in the database 414 as plaintext, in encrypted form, or as a hash (e.g., MD5 hash). The messaging system 436 communicates to the server engine 404 via message objects.

A message object comprises an action field, an ID field, a source field, a destination field, and an object field. The con-

14

tent of the action field is selected from a list of permitted actions, which among other actions includes: connect, disconnect, subscribe, unsubscribe, and post message. In addition, the actions include: determining if an IVM client is awake (i.e., pinging), disconnecting from the IVM client, processing an IVM client message, and notifying IVM clients if the IVM server 202 goes down. The client messages include sending an instant voice message portions, checkin message, send message, set status message, send a phone command message, and send control parameters message. The content of the ID field represents a unique identifier for the message object. The content of the source field is a globally unique identifier ("GUID") that uniquely identifies the sender of the message. This unique identifier can be generated by any known way, including the Globally Unique ID function call available in the Microsoft Windows and Microsoft NET environments. In some circumstances, the source field is set to a special value to indicate that the sender of the message object is entitled to special privileges. The senders with special privileges are in fact IVM servers. This allows the IVM servers to broadcast messages to one another, subscribe to special events, and directly send messages to specific IVM servers. These privileges can depend upon whether the IVM servers are local servers or global servers. As an example, there can exist more than one local IVM server, each of these local IVM servers automatically has privileges to communicate to other local IVM server. On a global server system, a directory server can communicate with one or more transport servers. The content of the destination field is a GUID of an intended IVM recipient of the instant voice message. The content of the object field is a block of data being carried by the message object, which may be, for example, a digitized instant voice message. Depending on the circumstances in which the message object is sent, some of the message object fields may be left blank or ignored. For example, the message object may merely require an action to be performed based upon the GUID supplied. In this case, the action does not necessarily require any data to be sent or received and some of the message object's fields may be left blank or ignored.

Connection objects maintain the logical connections between the IVM server 202 and IVM clients 206, 208 connected to the IVM server 202. More specifically, a connection object comprises data representing the state of the connection and code (one or more methods) for establishing and maintaining the logical connections between the IVM server 202 and the IVM clients 206, 208 within the IVM system 200 of FIG. 2. The connection object can contain both data and/or commands, including information that describes the socket, the size of the data to be transferred, and the priority of the transfer (e.g., high, normal, low, unknown). On start up the local IVM server 202 generates and maintains a list for each IVM client 206, 208. The local IVM server 202 then waits to receive connection objects from the IVM clients 206, 208 that are stored in the respective lists, decodes the received connection objects to obtain specific requests, and then services the specific requests from the IVM clients 206, 208.

Further with reference to FIG. 4, the server engine 404 controls all other subsystems in the server communication platform 402, and it is responsible for startup and shutdown of the IVM server 202 and the IVM system 200. The client manager 406 controls the IVM clients 206, 208, providing contact presence (connection) information and message scheduling and delivery. The station manager 408 controls the individual legacy telephone 110 and coordinates its activity to work synchronously with the IVM client 208 and server 202. The gateway manager 410 enables the IVM server 202 to communicate with the legacy telephones, such as legacy tele-

phone 110. The control layer 426 comprises a plurality of server subsystems 428-434, each of which provides translation services to different proprietary and non-proprietary gateways 114, such as TPNC, MGCP, and MEGACO gateways. The proprietary server subsystems 428, 430 and non-proprietary server subsystems 432, 434 are connected to respective gateways 114 via the local IP network 204. The supplemental server subsystems 416 provide a number of required services such as display manager subsystem 418, dynamic host configuration protocol (i.e., "DHCP") subsystem 420, trivial file transfer protocol (i.e., "TFTP") server subsystem 422, and hypertext transfer protocol (i.e., "HTTP"). Each of the supplemental servers 418-424 in the subsystem 416 is used during the initial set-up of the IVM system 200. The boot-up process and allocation of IP addresses to IVM clients 206, 208 are performed through an LCD panel (not shown) associated with the local IVM server 202. The LCD manager 418 supports this boot-up process. The DHCP server 420 is used to allocate IP addresses as required and allows the advanced configuration of network settings in the instant voice messaging system. The TFTP server 422 provides a TCP/IP file transfer capability. Lastly, the HTTP server 424 provides services for a web server.

FIG. 5 is an exemplary illustration of a global instant voice messaging (IVM) system 500, according to the present invention. In the global IVM system 500, the local IVM system 200 is depicted as a local IVM system 510, which is connected to a packet-switched network 102 (i.e., Internet). The global IVM system 500 comprises the local IVM system 510, global IVM server system 502, and global IVM clients 506 and 508 that are optionally connected via local IP network 504. The global IVM server system 502 is connected to the IP network (i.e., Internet) 102 for enabling the local IVM clients 206, 208 and legacy telephone 110 in the local IVM system 510 to generate and send instant voice messages to the global IVM clients 506, 508, as well as the local IVM clients 206, 208 to receive instant voice messages from the global IVM clients 506, 508. The implementation of the global instant voice messaging for the IVM client 208 will be described first and will be followed by the implementations for IVM client 206 and legacy telephone 110, with reference to the global IVM system 500 depicted in FIG. 5. Thereafter, instant voice messaging for global clients 506 and 508 will be described according to the present invention. These implementations implement a "record mode" of the instant voice messaging according to the present invention. Thereafter, there will lastly be described an "intercom mode" of the instant voice messaging according to the present invention.

Therefore, in operation of the IVM client 208 according to FIG. 5, the IVM client 208 is connected via the networks 204, 102 to the global IVM server system 502, which enables the global instant voice messaging functionality outside the local IVM system 510 over the network (i.e., Internet) 102. More specifically, the IVM client 208 requests from the global IVM server system 502 a global contact list (not shown) of global one or more IVM recipients with which the IVM client 208 may exchange instant voice messages. For the purposes of illustration, it is assumed that global IVM clients 506, 508 are in the contact list. The global IVM server system 502 stores and maintains this contact list. Thus, the global IVM server system 502 responds by transmitting the contact list to the IVM client 208. The IVM client 208 displays the contact list on its display 216. Alternatively, the global contact list may be replicated to the local IVM server 202 within the local IVM system 510, in which case the local IVM client 208 obtains the global contact list from the local IVM server 202. The user operates the IVM client 208 by using the input device 218 to

indicate a selection of one or more IVM recipients from the global contact list. Here, for the purposes of illustration it is again assumed that IVM client 208 selected global IVM clients 506, 508. The user selection is transmitted to the IVM server 202. The user selection also generates a start signal to the IVM client 208 that the user is ready to begin instant voice messaging. In response to the start signal, the IVM client 208 listens to the input audio device 212 and records the user's speech into a digitized audio file 210 (i.e., instant voice message) stored on the IVM client 208. The audio file 210 is finalized via a stop signal, which is generated by the user via the input device 218 or a preset time period without speech input via the input audio device 212. Once the recording is finalized, the IVM client 208 generates a send signal indicating that the digitized audio file 210 (instant voice message) is ready to be sent to the selected one or more IVM recipients. The user generates the send signal when the user operates the IVM client 208 via the input device 218. The IVM client 208 transmits the digitized audio file 210 and the send signal to the global IVM server system 502 via the local IP network 204 and the global IP network 102. After receiving the audio file 210, the global IVM server system 502 delivers the transmitted instant voice message to the selected one or more recipients (e.g., IVM clients 506 and 508) via the IP network 102. The one or more recipients are enabled to display an indication that the instant voice message has been received and audibly play the instant voice message to an associated user. It is noted that if a recipient IVM client 506, 508 is not currently connected to the global IVM server system 502, the global IVM server system 502 temporarily saves the instant voice message and delivers it to the global IVM client 506, 508 when the IVM client connects to the global IVM server system 502.

There are several embodiments for the operation of the IVM client (VoIP telephone) 206 within the global IVM system 500 of FIG. 5, according to the present invention. In the first embodiment, the VoIP telephone 206 is a standalone IVM client 206 enabled for instant voice messaging according to the present invention. In the second embodiment, the VoIP telephone 206 operates synchronously with the IVM client 208 to enable instant voice messaging according to the present invention. Thus, in operation according to the first embodiment in FIG. 5, the IVM client 206 is connected via the networks 204, 102 to the global IVM server system 502, which enables instant voice messaging functionality over the IP network (Internet) 102. As mentioned previously, the IVM client 206 is also connected to the local IVM server 202. The IVM client 208 requests from the global IVM server system 502 a global contact list (not shown) of the global one or more IVM recipients with which the IVM client 206 may exchange instant voice messages. For the purposes of illustration, it is assumed that the global IVM clients 506, 508 are in the contact list. The global IVM server system 502 stores and maintains this contact list. Thus, the global IVM server system 502 responds by transmitting the global contact list to the IVM client 206. Alternatively, the global contact list may be replicated to the local IVM server 202 within the local IVM system 510, in which case the local IVM client 206 obtains the global contact list from the local IVM server 202. The IVM client 206 displays a list of the one or more IVM recipients on its associated display. The user operates the IVM client 206 by using a keypad on the VoIP telephone 206 to indicate a selection of one or more IVM recipients from the list. The VoIP telephone 206 transmits the selection to the global IVM server system 502. The user selection also generates a start signal to the IVM client 206 indicating the user is ready to begin instant voice messaging according to the

17

present invention. The user speaks into the handset of the IVM client 206 or a speakerphone on the IVM client 206. Although not shown in FIG. 5, the VoIP telephone 206 may provide a dedicated storage device, which in response to the start signal records an audio file, similar to the audio file 210 in the IVM client 208. The audio file is finalized via a stop signal. The stop signal is generated when the user presses a button on the keypad, a preset time period without speech input to the VoIP telephone 206, or when the user returns the handset to the cradle of the VoIP telephone 206. Once the recording of the user's speech is complete, a send signal is generated indicating that the instant voice message is ready to be sent to the selected recipients. The user generates the send signal when the user presses a button on the keypad or returns the handset of the VoIP telephone 206 to it cradle. In response to the send signal, the IVM client 206 sends the recorded audio file (instant voice message) to the global IVM server system 502 via the networks 204, 102 for delivery to the selected one or more IVM recipients. The global IVM server system 502 thereafter delivers the instant voice message to the selected one or more recipients (e.g., IVM clients 506 and 508) via the IP network 102. As before, the one or more recipients are enabled to display an indication that the instant voice message has been received and audibly play the instant voice message. If a recipient IVM client is not currently connected to the global IVM server system 502, the global IVM server system 502 temporarily saves the instant voice message and delivers it to the IVM client when the IVM client connects to the global IVM server system 502.

In the second embodiment of the IVM client 206 according to FIG. 5, the VoIP telephone 206 operates synchronously with the IVM client 208 to enable global instant voice messaging according to the present invention. Thus, in operation according to the second embodiment in FIG. 5, the VoIP telephone 206 is connected over the network 204 to the IVM client 208 and the IVM client 208 is connected via the networks 204, 102 to the global IVM server system 502, which enables instant voice messaging functionality over the IP network (Internet) 102. The VoIP telephone 206 cooperates with the IVM client 208 to record and send a global instant voice message outside the local IVM system 510. The IVM client 208 displays a global contact list of IVM recipients (not shown) on the display device 216 provided by the global IVM server system 502, as described hereinabove. Alternatively, the global contact list may be replicated to the local IVM server 202 within the local IVM system 510, in which case the IVM client 208 obtains the global contact list from the local IVM server 202. The user operates the IVM client 208 by using the input device 218 to indicate a selection of one or more IVM recipients from the contact list. The user selection generates a start signal in the IVM client 208 indicating that the user is ready to begin instant voice messaging according to the present invention. In response to the start signal, the IVM client 208 generates audio file 210 to record an instant voice message and transmits a ring signal to the VoIP telephone 206. As the user picks up the handset of the VoIP telephone 206 (off-hook), a connection is established via the network 204 between the local IVM client 208 and the VoIP telephone 206. Thereafter, the VoIP telephone 206 forwards the user's speech to the IVM client 208 for storage into the audio file 210. The audio file 210 is finalized by returning the handset its cradle (on-hook) or by pressing a designated button on the keypad VoIP telephone 206, which transmits the stop signal to the IVM client 208. Returning the handset to its cradle preferably generates a send signal to the IVM client 208. The IVM client thereafter transmits the recorded audio file 210 (instant voice message) to the global IVM server

18

system 502 via networks 204, 102 for delivery to the selected one or more IVM recipients. Alternatively, the user may press a key on the keyboard 218 to initiate the send signal. In response to the send signal, the IVM client 208 sends the recorded audio file to the global IVM server system 502 for delivery to the selected one or more IVM recipients. The global IVM server system 502 thereafter delivers the instant voice message to the selected one or more recipients (e.g., IVM clients 506 and 508) via the IP network 102. As before, the one or more IVM recipients are enabled to display an indication that the instant voice message has been received and audibly play the instant voice message. If a recipient IVM client is not currently connected to the global IVM server system 502, the global IVM server system 502 temporarily saves the instant voice message and delivers it to the IVM client when the IVM client connects to the global IVM server system 502.

In operation of the legacy telephone 110 according to FIG. 5, the legacy telephone 110 is connected to the local IVM client 208 via media gateway 114, legacy switch 112 and network 204. The legacy telephone 110 cooperates with the IVM client 208 to record and send an instant voice message outside the local IVM system 510. More specifically, the legacy telephone 110 is used as a recording/listening device for recording or listing to instant voice messages, while the IVM client 208 is used for displaying and selecting instant voice message recipients as described hereinabove. Thus, in operation the IVM client 208 requests from the global IVM server system 502 a global contact list of global one or more IVM recipients with which the IVM client 208 may exchange instant voice messages. Alternatively, the global contact list may be replicated to the local IVM server 202 within the local IVM system 510, in which case the IVM client 208 obtains the global contact list from the local IVM server 202. The IVM client 208 displays the global list of IVM recipients, as described hereinabove. The user operates the IVM client 208 to indicate a selection of one or more IVM recipients from the global contact list. The IVM client 208 transmits the user selection to the global IVM server system 502. The user selection generates a start signal in the IVM client 208 indicating that the user is ready to begin instant voice messaging according to the present invention. In response to the start signal, the IVM client 208 transmits an emulation code to the legacy telephone 110 to ring, thereby indicating to the user the global IVM system 500 is ready to record an instant voice message. As the user picks up the handset of the legacy telephone 110 (off-hook), a connection is established via the network 204 between the legacy telephone 110 and the IVM client 208. Thereafter, the user's speech is transmitted from the legacy telephone 110 to the IVM client 208 for storage into the digitized audio file 210 (i.e., instant voice message). The audio file 210 is finalized by returning the handset of the legacy telephone 110 to its cradle (on-hook) or by pressing a designated button on the keypad of the legacy telephone 110, which transmits a stop signal to the IVM client 208. Returning the handset to its cradle may also generate a send signal to the IVM client 208 to transmit the recorded audio file (instant voice message) to the global IVM server system 502 for delivery to the selected one or more IVM recipients. Alternatively, the send signal is preferably generated from the IVM client 208 as described hereinabove. The global IVM server system 502 thereafter delivers the instant voice message to the selected one or more IVM recipients via the IP network (Internet) 102. The one or more recipients are enabled to display an indication that the instant voice message has been received and audibly play the instant voice message. If a recipient IVM client is not currently connected to the global

19

IVM server system **502**, the global IVM server system **502** temporarily saves the instant voice message and delivers it to the IVM client when the IVM client connects to the global IVM server **502**.

Further with reference to FIG. **5**, the instant voice messaging for global clients **506** and **508** will be described according to the present invention. In a first embodiment, each of the global IVM clients **506**, **508** is enabled to independently send an instant voice message. The IVM clients **506**, **508** have like peripheral devices and functionality described respectively with reference to local IVM clients **206**, **208** in FIG. **2**. In second embodiment described below, the VoIP telephone **506** operates in conjunction with the IVM client **508** to send an instant voice message. Therefore, in operation of the global IVM clients **506** and **508** according the first embodiment in FIG. **5**, the IVM clients **506**, **508** are connected via the networks **204**, **102** to the global IVM server system **502**, which enables the global instant voice messaging functionality outside the local IVM system **510** over the network (i.e., Internet) **102**. Each of the global IVM clients **506**, **508** is enabled to request from the global IVM server system **502** a contact list (not shown) of global one or more IVM recipients with which each of the global IVM client **506**, **508** may exchange instant voice messages. For the purposes of this illustration, it is assumed that the IVM clients **206** and **208** within the local IVM system **510** are in the contact list for each global IVM client **506**, **508**. The global IVM server system **502** stores and maintains the foregoing contact list for each global IVM client **506**, **508**. Upon request, the global IVM server system **502** responds by transmitting the contact list to each of the IVM clients **506**, **508**. Each of the IVM clients **506**, **508** displays the contact list on its display. The user operates the IVM client **506**, **508** to indicate a selection of one or more IVM recipients from the contact list. Each of the global IVM clients **506**, **508** transmits the user selection to the global IVM server system **502**. The user selection also generates a start signal to the IVM clients **506**, **508** that the user is ready to begin instant voice messaging. In response to the start signal, the IVM clients **506**, **508** record the user's speech into a digitized audio file (i.e., instant voice message) stored on the global IVM clients **506**, **508**. The audio file is finalized via a stop signal, which is generated by the user by operating the global IVM client **506**, **508**. Once the recording is finalized, the IVM client **506**, **508** generates a send signal indicating that the digitized audio file (instant voice message) is ready to be sent to the selected one or more recipients. The user generates the send signal when the user operates the global IVM client **506**, **508**. The IVM client **208** transmits the digitized audio file and the send signal to the global IVM server system **502**. After receiving the audio file, the global IVM server system **502** delivers the transmitted instant voice message to the local IVM server **202** in the local IVM system **510** for delivery to the selected one or more recipients (e.g., local IVM clients **206** and **208**) via the local IP network **204**. The one or more recipients IVM **206**, **208** are enabled to display an indication that the instant voice message has been received and audibly play the instant voice message to an associated user. It is noted that if a recipient IVM client **206**, **208** is not currently connected to the local IVM server **202**, the IVM server **202** temporarily saves the instant voice message and delivers it to the local IVM client **206**, **208** when the IVM client connects to the local IVM server **202**.

In the second embodiment of the IVM client **506** according to FIG. **5**, the VoIP telephone **506** operates synchronously with the IVM client **508** to enable global instant voice messaging according to the present invention. In this embodiment, the VoIP telephone **506** and the IVM client **508** may be

20

located in a user's residence and be connected to a local IP network **504**. This local IP network **504** can be a WiFi network or a local area network (i.e., LAN), which is also within the user's residence. The local IP network **504** may be connected to the IP network (Internet) **102** via a digital subscriber line (i.e., DSL) connection, cable connection, dialup connection, or the like. As noted above, the IVM clients **506**, **508** have like peripheral devices and functionality described respectively with reference to local IVM clients **206**, **208** in FIG. **2**. Thus, in operation according to this embodiment in FIG. **5**, the global IVM client **508** requests from the global IVM server system **502** a contact list of global one or more IVM recipients with which each of the global IVM client **508** may exchange instant voice messages. For the purposes of this illustration, it is assumed that the IVM clients **206** and **208** within the local IVM system **510** are in the contact list for the global IVM client **508**. The global IVM server system **502** stores and maintains the foregoing contact list for the global IVM client **508**. The IVM client **508** displays a contact list of IVM recipients on the associated display device provided by the global IVM server system **502**, as described hereinabove. The user operates the IVM client **508** by using the associated input device to indicate a selection of one or more IVM recipients from the contact list. The user selection generates a start signal in the IVM client **508** indicating that the user is ready to begin instant voice messaging according to the present invention. In response to the start signal, the IVM client **508** generates audio file to record an instant voice message and transmits a ring signal to the VoIP telephone **506** via local IP network **504**. As the user picks up the handset of the VoIP telephone **206** (off-hook), a connection is established via the local network **504** between the local IVM client **508** and the VoIP telephone **506**. Thereafter, the VoIP telephone **506** forwards the user's speech to the IVM client **508** for storage into the audio file at the IVM client **508**. The audio file is finalized by returning the handset its cradle (on-hook) or by pressing a designated button on the keypad associated with the VoIP telephone **506**, which transmits the stop signal to the IVM client **508**. Returning the handset to its cradle preferably generates a send signal to the IVM client **508**. The IVM client thereafter transmits the recorded audio file (instant voice message) to the global IVM server system **502** for delivery to the selected one or more IVM recipients. Alternatively, the user may press a key on the input device associated with the IVM client **508** to initiate the send signal. In response to the send signal, the IVM client **508** sends the recorded audio file to the global IVM server system **502** for delivery to the selected one or more IVM recipients. The global IVM server system **502** thereafter transmits the instant voice message to the local IVM server **202** for delivery selected one or more recipients (e.g., local IVM clients **206** and **208**) via the local IP network **204**. As before, the one or more recipients are enabled to display an indication that the instant voice message has been received and audibly play the instant voice message. If a recipient IVM client is not currently connected to the local IVM server **202**, the local IVM server **202** temporarily saves the instant voice message and delivers it to the IVM client when the IVM client connects to the local IVM server **202**.

Lastly with reference to FIG. **5**, in addition to the "record mode" of instant voice messaging as described above, the instant voice messaging system **500** also supports an "intercom mode" of the instant voice messaging. The "intercom mode" represents real-time instant voice messaging. In the "intercom mode," instead of creating an audio file as described hereinabove, one or more buffers (not shown) of a predetermined size are generated. The buffers may be gener-

ated in any one of the IVM clients **206**, **208**, **506** and **508**, depending on how the global IVM system **500** is defined. The one or more buffers are used to automatically write successive portions of the instant voice message. Once a first buffer is full, i.e., input audio of the predetermined size is written to the buffer, the content of the first buffer is automatically transmitted. If the transmission is generated at a local IVM client **206**, **208** and destined for one or more local IVM recipients, the content of the first buffer is transmitted to the local IVM server **202** for delivery to the local one or more recipients. If the transmission is generated at a local IVM client **206**, **208** and destined for one or more global IVM recipients **506**, **508**, the content of the first buffer is transmitted to the global IVM server system **502** for delivery to the one or more global recipients. In addition, if the transmission is generated at a global IVM client **506**, **508** and destined for the other global IVM clients, the content of the first buffer is transmitted to the global IVM server system **502**, such as for example clients **506**, **508**. Lastly, if the transmission is generated at a global IVM client **506**, **508** and destined for the local IVM clients **206**, **208**, the content of the first buffer is transmitted to the global IVM server system **502** and further transmitted by the global IVM server **502** to the local IVM server **202** for delivery to clients **206**, **208** within the local IVM system **510**. A second buffer is meanwhile written with the next successive portion of input audio. Once, the second buffer is full, i.e., input audio of the predetermined size is written to the buffer, the content of the second buffer is transmitted in similar fashion to the first buffer. If the entire instant voice message or a successive portion thereof (such as a last successive portion in the instant voice message) written to either buffer is smaller than the predetermined size, then the buffered content of less than the predetermined size is automatically transmitted to the IVM server **202**. The foregoing buffering using the first and second buffers is repeated until the entire instant voice message has been transmitted as described above. It is noted that the invention is not limited to a particular number of buffers. The foregoing buffering and transmission allows a "real-time" instant voice message to be transmitted to the one or more local, as well as global, IVM recipients. The "intercom mode" may be designated as a default mode when an IVM recipient is on-line, while the "record mode" may be designated as a default if the IVM recipient is unavailable, i.e., not on-line. The user may easily change the "intercom mode" to the "record mode" on the respective IVM client **206**, **208**, **506**, **508**. Finally, the audio contents of the buffers may be signal processed (for clarity), encrypted and compressed before transmission, as was described previously.

FIG. 6 is an exemplary detailed illustration **600** of the global IVM server system **502** depicted in FIG. 5, according to the present invention. More specifically, the local IVM system **510** described in FIG. 5 is connected via the IP network (Internet) **102** to the global IVM server system **502**. The global IVM server system **502** comprises an IVM transport server mesh **602** and an IVM directory server **608**. The IVM transport server mesh **602** comprises a plurality of interconnected IVM transport servers **604**, **606**. Although the mesh **602** is depicted as having two IVM transport servers **604**, **606**, it is to be understood that as many IVM transport servers as are desired or required for redundancy and load balancing may be interconnected in a mesh. The IVM transport servers **604**, **606** may be centrally located and configured to communicate (i.e., forward and receive messages) with local IVM clients **206**, **208**, local IVM server **202** and global IVM client **506**, **508** (not depicted in FIG. 6). The plurality of IVM transport servers **604**, **606** in the IVM transport server mesh **602** permits load balancing and redundancy in the global IVM

system **500**. The directory server **608** maintains a transport server list of all the IVM transport servers **604**, **606** currently connecting to the mesh **602**. Each of the IVM transport servers **604**, **606** first connects to the directory server **608**. The directory server **608** informs each of the connecting IVM transport servers **604**, **606** of all the other IVM transport servers currently in the mesh **602** based on an active list (not shown) of transport servers **604**, **606** in the mesh **602**. The connecting IVM transport server then connects to each of the IVM transport servers in the transport server list, resulting in an interconnected mesh **602** of IVM transport servers **604**, **606**. The IVM transport servers **604**, **606** and the IVM directory server **608** communicate via messages.

Further with reference to FIG. 6, the IVM transport servers **604**, **606** connected in the mesh **602** share a database (not shown) of IVM clients, so that each IVM transport server **604**, **606** refers to the same client database. It is preferable that each IVM transport server **604**, **606** maintains its own copy of the client database, which is mirrored and replicated conventionally amongst the IVM transport servers **604**, **606** in the mesh **602**. The client database may further be replicated to the local IVM server **202**. Alternatively, the client database is stored on a separate file server (not shown) in data communication with the IVM transport servers **604**, **606** over a network (not shown).

FIG. 7 is an exemplary detailed illustration of a transport server **604**, **606** depicted in FIG. 6, according to the present invention. The IVM transport server **604**, **606** is a general-purpose programmable computer comprising a network interface (not shown) connected to IP network (Internet) **102**, a communication platform **702**, a message database **712**, and a messaging system **714**. The communication platform **702** comprises a server engine **704**, which controls a user manager **706**, a local server manager **708**, and a storage manager **710**. The messaging system **714** and the server engine **704** communicate via standard inter-process communication. The storage manager **710** handles retrieving, sending, and storing of messages, including instant voice messages and attachments thereto, to/from the message database **712**. The user manager **706** is responsible for creating/maintaining IVM clients **206**, **208**, **506**, **508**, identifying them and relaying their status to the server engine **704**. When an IVM client communicates an instant voice message within the global IVM system **500**, the user manager **706** notifies the server engine **704** whether the one or more recipients are unavailable, and thereby the instant voice message is saved in the message database **712**. When the one or more IVM recipients become available, the user manager **706** notifies the server engine **704**, which instructs the storage manager **710** to retrieve any undelivered instant voice messages for the one or more recipients and delivers the instant voice messages to the designated one or more IVM recipients. The local server manager **708** is responsible for creating/maintaining and providing the status of available local IVM servers, such as IVM server **202** in FIG. 2. The availability status of the local IVM servers is checked periodically and updated.

FIG. 8 is an exemplary detailed illustration of a directory server **608** depicted in FIG. 6, according to the present invention. The directory server **608** is a general-purpose programmable computer equipped with a network interface (not shown) connected to IP network (Internet) **102**, a messaging system **812**, and a communication platform **802**. The communication platform **802** comprises a server engine **804**, which controls a local server manager **806**, a user manager **808**, and a transport manager **810**. The messaging system **812** and the server engine **804** communicate via standard inter-process communication. The transport manager **810** main-

23

tains the status of the IVM transport servers **604, 606** in the IVM transport server mesh **602** within the global IVM system **500** and using a load-balancing mechanism distributes instant voice messages to available transport server **604, 606** for routing to the one or more IVM recipients. The user manager **808** is responsible for creating/maintaining IVM clients **206, 208, 506, 508**, identifying and relaying their status via the server engine **804** to the IVM transport server **604, 606** to be used. The local server manager **806** is responsible for creating/maintaining and providing the status of available local IVM servers, such as IVM server **202** in FIG. 2. The availability status of the local IVM servers is checked periodically and updated.

FIG. 9 illustrates an exemplary a global instant voice messaging (IVM) system **900**, which comprises a plurality of local IVM systems and a plurality of global IVM clients, according to the present invention. In the global IVM system **900**, there are depicted a plurality of local IVM systems **902, 910** connected to the global IP network **102**. The internal representation and functionality of each local IVM system **902, 904** is identical to the local IVM system **510** described with reference to FIG. 5. In global IVM system **900** of FIG. 9, there are also depicted a plurality of global IVM clients **918-928** and a global IVM server system **502** connected to the global IP network (i.e., Internet) **102**. The internal representations of the global IVM client **918-928** and the global IVM server system **502** are identical to the respective IVM client **508** (and/or IVM client or **506**) and the global IVM server system **502** described with reference to FIG. 5. In the local IVM system **902**, each local IVM client **206, 208** is enabled to request local IVM recipients from the local IVM server **202** and global IVM recipients from either the global IVM server system **502** or the local IVM server **202**. For example, the local IVM client **1A 208** displays a list **904** to a user, comprising both local and global IVM recipients. More specifically, the list **904** enables IVM client **1A** to send instant voice messages according to the present invention to local IVM clients **1B 208** and **1C 206**, global IVM client **C 922** and global IVM client **2A 208** in the local IVM system **910**. Similar lists **906-916** are displayed to the users of the respective IVM clients **1B-1C** in local IVM system **902**, and **2A-2C** in local IVM system **910**. In addition, the global clients **A-F 918-928** are enabled to request IVM recipients from the global IVM server system **502** and display the respective lists of IVM recipients **930-940** on the respective IVM clients **918-928**.

While the invention has been particularly shown and described with regard to preferred embodiments thereof, it will be understood by those skilled in the art that the foregoing and other changes in form and details may be made therein without departing from the spirit and scope of the invention.

Having thus described our invention, what we claim as new, and desire to secure by Letters Patent is:

1. An instant voice messaging system for delivering instant messages over a packet-switched network, the system comprising:
 - a client connected to the network, the client selecting one or more recipients, generating an instant voice message therefor, and transmitting the selected recipients and the instant voice message therefor over the network; and
 - a server connected to the network, the server receiving the selected recipients and the instant voice message therefor, and delivering the instant voice message to the selected recipients over the network, the selected recipients enabled to audibly play the instant voice message, and the server temporarily storing the instant voice mes-

24

sage if a selected recipient is unavailable and delivering the stored instant voice message to the selected recipient once the selected recipient becomes available.

2. The instant voice messaging system according to claim 1, wherein the packet-switched network is a local network.
3. The instant voice messaging system according to claim 1, wherein the packet-switched network is the Internet.
4. The instant voice messaging system according to claim 1, wherein the client requests a list of recipients associated with the client from the server and the server transmits the list of recipients to the client for selection of the one or more recipients.
5. The instant voice messaging system according to claim 1, wherein the server delivers the instant voice message to the selected recipients that are available.
6. The instant voice messaging system according to claim 1, wherein the client records the instant voice message in an audio file, transmits the audio file to the server, and the server delivers the audio file to the selected recipients, the selected recipients being enabled to audibly play the audio file.
7. The instant voice messaging system according to claim 6, wherein the client signal processes, compresses and encrypts the audio file, and the selected recipients being enabled to decrypt and decompress the audio file before audibly playing the audio file.
8. The instant voice messaging system according to claim 1, wherein the client buffers each of a plurality of successive portions of the instant voice message as the instant message is recorded, and the client transmits each successive buffered portion to the server for delivery to the to the selected recipients, the selected recipients being enabled to audibly playing each successive portion as it is delivered.
9. The instant voice messaging system according to claim 1, wherein the client is enabled to attach one or more files to the instant voice message and the selected recipients are enabled to store or display the one or more attached files.
10. The instant voice messaging system according to claim 1, the system further comprising a public switched telephone network (PSTN) telephone connected to the network to provide input audio of the instant voice message to the client.
11. The instant voice messaging system according to claim 1, the system further comprising a voice-over-internet-protocol (VoIP) telephone connected to the network to provide input audio of the instant voice message to the client.
12. An instant voice messaging system for delivering instant messages over a packet-switched network enabling public switched telephone network (PSTN) support, the system comprising:
 - a PSTN telephone connected to the network for providing input audio;
 - a client connected to the network, the client selecting one or more recipients, generating an instant voice message therefor using the input audio provided by the PSTN telephone, and transmitting the selected recipients and the instant voice message therefor over the network;
 - a server connected to the network, the server receiving the selected recipients and the instant voice message therefor, and delivering the instant voice message to the selected recipients over the network, the selected recipients being enabled to audibly play the instant voice message, and the server temporarily storing the instant voice message if a selected recipient is unavailable and delivering the stored instant voice message to the selected recipient once the selected recipient becomes available.

25

13. An instant voice messaging system for delivering instant messages over a packet-switched network, the system comprising:

a voice-over-internet-protocol (VoIP) telephone connected to the network for providing input audio;

a client connected to the network, the client selecting one or more recipients, generating an instant voice message therefor using the input audio provided by the VoIP telephone, and transmitting the selected recipients and the instant voice message therefor over the network;

a server connected to the network, the server receiving the selected recipients and the instant voice message therefor, and delivering the instant voice message to the selected recipients over the network, the selected recipients being enabled to audibly play the instant voice message, and the server temporarily storing the instant voice message if a selected recipient is unavailable and delivering the stored instant voice message to the selected recipient once the selected recipient becomes available.

14. An instant voice messaging system for delivering instant messages over a plurality of packet-switched networks, the system comprising:

a client connected to a local network, the client selecting one or more external recipients connected to an external network outside the local network, generating an instant voice message therefor, and transmitting the selected recipients and the instant voice message therefor over the local network and the external network; and

a server connected to the external network, the server receiving the selected recipients and the instant voice message therefor, and delivering the instant voice message to the selected recipients over the external network, the selected recipients being enabled to audibly play the instant voice message, and the server temporarily storing the instant voice message if a selected recipient is unavailable and delivering the stored instant voice message to the selected recipient once the selected recipient becomes available.

15. The instant voice messaging system according to claim 14, the client further selects one or more local recipients connected to the local network and transmits the selected local recipients and the instant voice message therefor over the local network, wherein the system further comprises:

a local server connected to the local network, the local server receiving the selected local recipients and the instant message therefor from the client, and delivering the instant voice message to the selected local recipients over the local network, the selected local recipients being enabled to audibly play the instant voice message.

16. The instant voice messaging system according to claim 14, wherein the local network is a network within an enterprise.

17. The instant voice messaging system according to claim 14, wherein the external network is the Internet.

18. The instant voice messaging system according to claim 14, wherein the client requests a list of recipients associated with the client from the server and the server transmits the list of recipients to the client for selection of the one or more recipients.

19. The instant voice messaging system according to claim 14, wherein the server delivers the instant voice message to the selected recipients that are available.

20. The instant voice messaging system according to claim 14, wherein the client records the instant voice message in an audio file, transmits the audio file to the server, and the server

26

delivers the audio file to the selected recipients, the selected recipients being enabled to audibly play the audio file.

21. The instant voice messaging system according to claim 20, wherein the client signal processes, compresses and encrypts the audio file, and the selected recipients are enabled to decrypt and decompress the audio file before audibly playing the audio file.

22. The instant voice messaging system according to claim 14, wherein the client buffers each of a plurality of successive portions of the instant voice message as the instant message is recorded, and the client transmits each successive portion to the server for delivery to the selected recipients, the selected recipients being enabled to audibly playing each successive portion as it is delivered.

23. The instant voice messaging system according to claim 14, wherein the client is enabled to attach one or more files to the instant voice message and the selected recipients are enabled to store or display the one or more attached files.

24. The instant voice messaging system according to claim 14, the system further comprising a public switched telephone network (PSTN) telephone connected to the local network to provide input audio of the instant voice message to the client.

25. The instant voice messaging system according to claim 14, the system further comprising a voice-over-internet-protocol (VoIP) telephone connected to the local network to provide input audio of the instant voice message to the client.

26. An instant voice messaging system for delivering instant messages over a plurality of packet-switched networks enabling public switched telephone network (PSTN) support, the system comprising:

a PSTN telephone connected to a local network for providing input audio;

a client connected to the local network, the client selecting one or more external recipients connected to an external network outside the local network, generating an instant voice message therefor using the input audio provided by the PSTN telephone, and transmitting the selected recipients and the instant voice message therefor over the local network and the external network;

a server connected to the external network, the server receiving the selected recipients and the instant voice message therefor, and delivering the instant voice message to the selected recipients over the external network, the selected recipients being enabled to audibly play the instant voice message, and the server temporarily storing the instant voice message if a selected recipient is unavailable and delivering the stored instant voice message to the selected recipient once the selected recipient becomes available.

27. An instant voice messaging system for delivering instant messages over a plurality of packet-switched networks, the system comprising:

a voice-over-internet-protocol (VoIP) telephone connected to a local network for providing input audio;

a client connected to the local network, the client selecting one or more external recipients connected to an external network outside the local network, generating an instant voice message therefor using the input audio provided by the VoIP telephone, and transmitting the selected recipients and the instant voice message therefor over the local network and the external network;

an server connected to the external network, the external server receiving the selected recipients and the instant voice message therefor, and delivering the instant voice message to the selected recipients over the external network, the selected recipients being enabled to audibly

27

play the instant voice message, and the server temporarily storing the instant voice message if a selected recipient is unavailable and delivering the stored instant voice message to the selected recipient once the selected recipient becomes available.

28. An instant voice messaging system for delivering instant messages over a plurality of packet-switched networks, the system comprising:

a client connected to an external network, the client selecting one or more recipients connected to a local network, generating an instant voice message therefor, and transmitting the selected recipients and the instant voice message therefor over the external network; and

a external server system connected to the external network, the external server system receiving the selected recipients and the instant voice message, and routing the selected recipients and the instant voice message over the external network and the local network;

a local server connected to the local network, the local server receiving the selected recipients and the instant voice message therefor, and delivering the instant voice message to the selected recipients over the local network, the selected recipients being enabled to audibly play the instant voice message, and the local server temporarily storing the instant voice message if a selected recipient is unavailable and delivering the stored instant voice message to the selected recipient once the selected recipient becomes available.

29. The instant voice messaging system according to claim 28, the client further selects one or more external recipients connected to the external and transmits the selected external recipients over the external network to the external server, and the external server receives the selected external recipients and delivers the instant voice message to the selected external recipients over the external network, the selected external recipients being enabled to audibly play the instant voice message.

30. The instant voice messaging system according to claim 28, wherein the local network is a network within an enterprise.

31. The instant voice messaging system according to claim 28, wherein the external network is the Internet.

32. The instant voice messaging system according to claim 28, wherein the client requests a list of recipients associated with the client from the external server system and the external server system transmits the list of recipients to the client for selection of the one or more recipients.

33. The instant voice messaging system according to claim 28, wherein the local server delivers the instant voice message to the selected recipients that are available.

34. The instant voice messaging system according to claim 28, wherein the client records the instant voice message in an audio file, transmits the audio file to the external server, the external server system routes the audio file to the local server, and the local server delivers the audio file to the selected recipients, the selected recipients being enabled to audibly play the audio file.

35. The instant voice messaging system according to claim 34, wherein the client signal processes, compresses and encrypts the audio file, and the selected recipients are enabled to decrypt and decompress the audio file before audibly playing the audio file.

36. The instant voice messaging system according to claim 28, wherein the client buffers each of a plurality of successive portions of the instant voice message as the instant message is recorded, and the client transmits each successive buffered portion to the external server system, the external server sys-

28

tem routes each successive portion to the local server, and the local server delivers each successive portion to the to the selected recipients, the selected recipients being enabled to audibly play each successive portion as it is delivered.

37. The instant voice messaging system according to claim 28, wherein the client is enabled to attach one or more files to the instant voice message and the selected recipients are enabled to store or display the one or more attached files.

38. The instant voice messaging system according to claim 28, the system further comprising a voice-over-internet-protocol (VoIP) telephone connected to the client via a local network, the client providing input audio of the instant voice message to the client via the local network.

39. The instant voice messaging system according to claim 28, wherein the external server system comprises:

a transport server mesh including a plurality of transport servers for routing instant voice messages;

a directory server for maintaining the transport server mesh and facilitating load-balancing of the instant voice messages within the transport server mesh.

40. A method for instant voice messaging over a packet-switched network, the method comprising:

selecting one or more recipients for instant voice messaging at a client;

generating an instant voice message for the selected recipients at the client;

transmitting the selected recipients and the instant voice message therefor over the network from the client to a server;

receiving the selected recipients and the instant voice message therefor at the server;

delivering the instant voice message from the server to the selected recipients over the network;

temporarily storing at the server the instant voice message if a selected recipient is unavailable;

delivering from the server the stored instant voice message to the selected recipient once the selected recipient becomes available; and

audibly playing the instant voice message at the selected recipients.

41. The method for instant voice messaging according to claim 40, wherein the method further comprises:

requesting from the client a list of recipients associated with the client from the server; and

transmitting from the server the list of recipients to the client for selection of the one or more recipients.

42. The method for instant voice messaging according to claim 40, wherein the method further comprises:

delivering the instant voice message from the server to the selected recipients that are available.

43. The method for instant voice messaging according to claim 40, wherein the method further comprises:

recording the instant voice message at the client in an audio file;

transmitting the audio file to the server;

delivering the audio file from the server to the selected recipients; and

audibly playing the audio file at the least one of the selected recipients.

44. The method for instant voice messaging according to claim 43, wherein the method further comprises:

signal processing, compressing and encrypting the audio file at the client;

decrypting and decompressing the audio file at the at least one selected recipient; and

audibly playing the decrypted and decompressed audio file at the least one of the selected recipients.

45. The method for instant voice messaging according to claim 40, further comprising:
 buffering each of a plurality of successive portions of the instant voice message at the client as the instant message is recorded;
 transmitting from the client each successive buffered portion to the server;
 delivering each successive portion from the server to the selected recipients, the selected recipients audibly playing each successive portion as it is delivered.

46. The method for instant voice messaging according to claim 40, wherein the method further comprises:
 attaching one or more files to the instant voice message at the client;
 storing or displaying the one or more attached files at the selected recipients.

47. The method for instant voice messaging according to claim 40, wherein the method further comprises:
 providing input audio of the instant voice message to the client from a public switched telephone network (PSTN) telephone connected to the network.

48. The method for instant voice messaging according to claim 40, wherein the method further comprises:
 providing input audio of the instant voice message to the client from a voice-over-internet-protocol (VoIP) telephone connected to the network.

49. A method for instant voice messaging over a packet-switched network enabling public switched telephone network (PSTN) support, the method comprising:
 providing input audio via a PSTN telephone connected over the network;
 selecting one or more recipients for instant voice messaging at a client;
 generating an instant voice message using the input audio from the PSTN telephone for the selected recipients at the client;
 transmitting the selected recipients and the instant voice message therefor over the network from the client to a server;
 receiving the selected recipients and the instant voice message therefor at the server;
 delivering the instant voice message from the server to the selected recipients over the network;
 temporarily storing at the server the instant voice message if a selected recipient is unavailable;
 delivering from the server the stored instant voice message to the selected recipient once the selected recipient becomes available; and
 audibly playing the instant voice message at selected recipients.

50. A method for instant voice messaging over a packet-switched network, the method comprising:
 providing input audio via a voice-over-internet-protocol (VoIP) telephone connected over the network;
 selecting one or more recipients for instant voice messaging at a client;
 generating an instant voice message using the input audio from the VoIP telephone for the selected recipients at the client;
 transmitting the selected recipients and the instant voice message therefor over the network from the client to a server;
 receiving the selected recipients and the instant voice message therefor at the server;
 delivering the instant voice message from the server to the selected recipients over the network;

temporarily storing at the server the instant voice message if a selected recipient is unavailable;
 delivering from the server the stored instant voice message to the selected recipient once the selected recipient becomes available; and
 audibly playing the instant voice message at the selected recipients.

51. A method for instant voice messaging over a plurality of packet-switched networks, the method comprising:
 selecting one or more external recipients for instant voice messaging at a client connected to a local network, the one or more external recipients connected to an external network outside the local network;
 generating an instant voice message for the selected external recipients at the client;
 transmitting the selected external recipients and the instant voice message therefor over the local network and the external network;
 receiving the selected external recipients and the instant voice message therefor at an external server connected to the external network;
 delivering the instant voice message to the selected external recipients over the external network;
 temporarily storing the instant voice message at the external server if a selected recipient is unavailable;
 delivering the stored instant voice message to the selected recipient once the selected recipient becomes available; and
 audibly playing the instant voice message at the selected external recipients.

52. The method for instant voice messaging according to claim 51, wherein the method further comprises:
 requesting from the external server a list of external recipients associated with the client; and
 transmitting the list of external recipients from the external server to the client for selection of the one or more external recipients.

53. The method for instant voice messaging according to claim 51, wherein the method further comprises:
 delivering the instant voice message from the external server to the selected recipients that are available.

54. The method for instant voice messaging according to claim 51, wherein the method further comprises:
 recording the instant voice message in an audio file at the client;
 transmitting the audio file to the external server;
 delivering the audio file to the selected recipients from the external server; and
 audibly playing the audio file at the selected recipients.

55. The method for instant voice messaging according to claim 54, wherein the method further comprises:
 signal processing, compressing and encrypting the audio file at the client; and
 decrypting and decompressing the audio file at the selected recipients; and
 audibly playing the decrypted and decompressed audio file at the selected recipients.

56. The method for instant voice messaging according to claim 51, wherein the method further comprises:
 buffering each of a plurality of successive portions of the instant voice message at the client as the instant message is recorded;
 transmitting from the client each successive portion to the external server;
 delivering each successive portion from the external server to the selected external recipients,

31

audibly playing each successive portion at the selected external recipients as it is delivered.

57. The method for instant voice messaging according to claim 51, wherein the method thither comprises:

attaching one or more files to the instant voice message; 5
storing or displaying the one or more attached files at the selected external recipients.

58. The method for instant voice messaging according to claim 51, wherein the method further comprises providing input audio of the instant voice message to the client from a public switched telephone network (PSTN) telephone over the local network. 10

59. The method for instant voice messaging according to claim 51, wherein the method further comprises providing input audio of the instant voice message to the client from a voice-over-internet-protocol (VoIP) telephone over the local network. 15

60. A method for instant voice messaging system over a plurality of packet-switched networks enabling public switched telephone network (PSTN) support, the method comprising: 20

providing input audio via a PSTN telephone connected to a local network;

selecting one or more external recipients for instant voice messaging at a client, the one or more external recipients connected to an external network outside the local network; 25

generating an instant voice message for the one or more external recipients using the input audio provided by the PSTN telephone; 30

transmitting the selected recipients and the instant voice message therefor over the local network and the external network;

receiving the selected recipients and the instant voice message therefor at a server connected to the external network; 35

delivering the instant voice message to the selected recipients from the server over the external network;

temporarily storing at the server the instant voice message if a selected recipient is unavailable; 40

delivering from the server the stored instant voice message to the selected recipient once the selected recipient becomes available; and

audibly playing the instant voice message at the selected recipients. 45

61. A method for instant voice messaging system over a plurality of packet-switched networks, the method comprising; 50

providing input audio via a voice-over-internet-protocol (VoIP) telephone connected to a local network;

selecting one or more external recipients for instant voice messaging at a client, the one or more external recipients connected to an external network outside the local network; 55

generating an instant voice message for the one or more external recipients using the input audio provided by the VoIP telephone;

transmitting the selected recipients and the instant voice message therefor over the local network and the external network; 60

receiving the selected recipients and the instant voice message therefor at a server connected to the external network;

delivering the instant voice message to the selected recipients from the server over the external network; 65

temporarily storing at the server the instant voice message if a selected recipient is unavailable;

32

delivering from the server the stored instant voice message to the selected recipient once the selected recipient becomes available; and

audibly playing the instant voice message at the selected recipients.

62. A method for instant voice messaging over a plurality of a plurality of packet-switched networks, the method comprising:

selecting one or more recipients connected to a local network at a client connected to an external network;

generating an instant voice message for the selected recipients at the client;

transmitting the selected recipients and the instant voice message therefor over the external network from the client to an external server system;

receiving the selected recipients and the instant voice message at the external server system;

routing the selected recipients and the instant voice message over the external network and the local network;

receiving the selected recipients and the instant voice message therefor at a local server connected to the local network;

delivering the instant voice message to the selected recipients over the local network;

temporarily storing the instant voice message at the local server if a selected recipient is unavailable;

delivering the stored instant voice message to the selected recipient once the selected recipient becomes available; and

audibly playing the instant voice message at the selected recipients.

63. The method for instant voice messaging according to claim 62, wherein the method further comprises:

requesting a list of recipients associated with the client from the external server system; and

transmitting the list of recipients from the external server system to the client for selection of the one or more recipients.

64. The method for instant voice messaging according to claim 62, wherein the method further comprises:

delivering the instant voice message from the local server to the selected recipients that are available.

65. The method for instant voice messaging according to claim 62, wherein the method further comprises:

recording the instant voice message in an audio file at the client;

transmitting the audio file from the client to the external server system;

routing the audio file from the external server system to the local server; and

delivering the audio file from the local server to the selected recipients; and

audibly playing the audio file at the selected recipients.

66. The method for instant voice messaging according to claim 65, wherein the method further comprises:

signal processing, compressing and encrypting the audio file at the client;

decrypting and decompressing the audio file at the selected recipients;

audibly playing the decrypted and decompressed audio file at the selected recipients.

67. The method for instant voice messaging according to claim 62, wherein the method further comprises:

buffering each of a plurality of successive portions of the instant voice message at the client as the instant message is recorded;

33

transmitting from the client each successive portion to the external server system;
routing each successive portion from the external server system to the local server;
delivering each successive portion from local server to the selected external recipients; and
audibly playing each successive portion at the selected recipients as it is delivered.
68. The method for instant voice messaging according to claim 62, wherein the method further comprises:
attaching one or more files to the instant voice message at the client;
storing or displaying the one or more attached files at the selected recipients.

34

69. The method for instant voice messaging according to claim 62, wherein the method further comprises:
providing input audio of the instant voice message from a voice-over-internet-protocol (VoIP) telephone to the client via a local network connecting the VoIP telephone to the client.
70. The method for instant voice messaging according to claim 62, wherein the method further comprises:
maintaining a transport server mesh including a plurality of transport servers for routing instant voice messages; and
load-balancing the instant voice messages within the transport server mesh.

* * * * *